



Discover more details and matching accessories online!

## Entry level model into professional counting, counting resolution of 30,000 points, verification optional

### Features

- The automatic reference weight optimisation of reference weight gradually improves the average piece weight value
- Programmable using numerical key pad:
  - required reference quantity
  - known reference weight
- Three displays for weight display (verifiable), reference weight, total pieces
- Fill-to-target function: Target count or target weight can be programmed. When the target weight is reached there is an audible and visual signal
- 10 memories for reference weights
- Counting results memory: adds up all individual piece counts, result is shown in total weight and total pieces

- Integrated ESD protection, which makes it ideal for weighing small plastic parts
- Energy management: Backlight turns off after 5 sec
- PRE-TARE function for manual subtraction of a known container weight, useful for checking fill-levels
- Changes from counting mode to weighing mode at the touch of a key
- Protective working cover included with delivery

### Technical data

- Large backlit LCD displays, digit height 18 mm
- Dimensions weighing surface, stainless steel, W×D 300×225 mm
- Overall dimensions W×D×H 300×330×110 mm
- Rechargeable battery pack integrated, as standard, operating time up to 200 h without backlight, charging time approx. 8 h
- Net weight approx. 4,0 kg
- Permissible ambient temperature -10 °C/40 °C

Note: Official verification is mandatory for commercial trade

STANDARD

OPTION

FACTORY

CXB-NM

Model	Weighing capacity [Max] kg	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Smallest part weight (Normal) g/piece	Counting resolution Points	Options	
							Verification  KERN	Calibr. Certificate DAkkS accr. KERN
<b>CXB 3K0.2</b>	3	0,2	-	-	2	15.000	-	963-127
<b>CXB 6K0.5</b>	6	0,5	-	-	5	12.000	-	963-128
<b>CXB 15K1</b>	15	1	-	-	10	15.000	-	963-128
<b>CXB 30K2</b>	30	2	-	-	20	15.000	-	963-128

Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order. The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.

<b>CXB 3K1NM</b>	3	1	1	20	10	3.000	965-227	963-127
<b>CXB 6K2NM</b>	6	2	2	40	20	3.000	965-228	963-128
<b>CXB 15K5NM</b>	15	5	5	100	50	3.000	965-228	963-128
<b>CXB 30K10NM</b>	30	10	10	200	100	3.000	965-228	963-128