# KERN **ALJ 310-4A**



Analytical balance with high weighing capacity, graphic display and convenient recipe function

Display

Display type

Display backlight
Display screen size



| Category          |                    |
|-------------------|--------------------|
| Brand             | KERN               |
| Product categoriy | Laboratory balance |
| Product group     | Analytical balance |
| Product family    | ALJ                |

| Measuring System                                      |                                  |
|---|----------------------------------|
| Construction type of the scale                        | Single-range balance             |
| Weighing system                                       | Force compensation               |
| Weighing capacity [Max]                               | 310 g                            |
| Weighing capacity [Max] (ct)                          | 1550 ct                          |
| Readability [d]                                       | 0,0001 g                         |
| Readability carat [d] (ct)                            | 0,001 ct                         |
| Reproducibility                                       | 0,0001 g                         |
| Linearity   | ± 0,0003 g                       |
| USP Minimum weight of sample (k = 2, U = 0.1%)        | 200 mg                           |
| Resolution  | 3.100.000                        |
| Adjustment options                                    | Internal calibration (automatic) |
| Automatic adjustment - Standard temperature deviation | 1,2 °C                           |
| Automatic adjustment - Standard time interval         | 3 h                              |
| Stabilization time                                    | 4 s                              |
| Warm-up time  | 8 h                              |
| Eccentric loading at 1/3 [Max]                        | 0,0003 g                         |
| Maximum creep (15 minutes)                            | 1 mg                             |
| Maximum creep (30 minutes)                            | 2 mg                             |
| Default unit  | g                                |
| Units   | g<br>mg<br>gn                    |

| dwt                 |
|---------------------|
| tl (Tw)             |
| tl (HK)             |
| ozt                 |
| tl (Singap, Malays) |
| ct                  |
| mo                  |
| lb                  |
| 07                  |

LCD graphic

132×38 mm

| ' '   |                 |
|---|-----------------|
| Display digit height - smallest digit                 | 4 mm            |
| Display digit height                                  | 15 mm           |
| Languages of the user interface                       | English         |
|   |                 |
| Construction  |                 |
| Dimension housing (W×D×H)                             | 210×340×330 mm  |
| Dimensions completely mounted (W×D×H)                 | 210×340×330 mm  |
| Dimensions rectangular draught shield - inner (W×D×H) | 160×170×225 mm  |
| Dimensions rectangular draught shield - outer (W×D×H) | 172×185×245 mm  |
| Dimensions weighing surface (Ø)                       | 80 mm           |
| Dimensions weighing surface                           | 80 mm           |
| Material housing                                      | plastic         |
| Material weighing plate                               | stainless steel |
| Material platform                                     | Stainless steel |
| Material draught shield                               | glass           |
| Material display housing                              | Plastics        |
| Level indicator                                       | ✓               |
| Levelling feet adjustable                             | ✓               |
|   |                 |

| Functions  |   |
|--|---|
| PreTare function   | ✓   |
| Recipe/summing level                                       | Rez B (Net-total, memory<br>with plain text<br>designations + setpoint,<br>also for printout) |
| Recipe weighing - number of database entries               | 99  |
| Recipe weighing - number of ingredients per database entry | 20  |
| Percentage determination                                   | ✓   |
| Dispensing function  | ✓   |

0,1 Nm

Transport safety lock - bolt torque

1

# KERN **ALJ 310-4A**



Analytical balance with high weighing capacity, graphic display and convenient recipe function

| Density determination   | ✓  |
|---|--|
| Tolerance weighing  | ✓  |
| Tolerance weighing - type of signal                               | acoustically visual                          |
| Underfloor weighing   | None   |
| Function for averaging under unstable weighing conditions         | /  |
| Capacity - Display  | ✓  |
| Standby function  | ✓  |
| Counting function   | ✓  |
| Counting resolution (laboratory conditions)                       | 310.000                                      |
| Counting reference weight can be entered                          | /  |
| Smallest piece weight when piece counting - laboratory conditions | 1 mg   |
| Smallest piece weight when piece counting - normal conditions     | 10 mg  |
| Reference quantity  | 10, 25, 50, 100, n (any<br>number of pieces) |
| Auto-off interval(s) in mains power mode                          | off<br>5 min<br>2 min<br>15 min              |
| Tare function   | manual (multi)                               |
| Number of keys for operation                                      | 6  |

| Interface  |                 |
|------------|-----------------|
| Interfaces | RS-232 standard |

| Power Supply  |                               |
|---|-------------------------------|
| Supplied power supply   | Power supply unit             |
| Plug-in power supply type   | Power adapter                 |
| Plug-in power supply / adapter for countries - included with the delivery | EURO<br>AUS<br>UK<br>US<br>CH |
| Plug-in power supply / adapter for countries - optional                   | EURO<br>UK<br>US<br>CH        |
| Input voltage power supply / power [Max]                                  | country dependent             |
| Input voltage device / power [Max]  | 24 V 1 A                      |

| Environmental conditions    |       |
|-----------------------------|-------|
| Ambient temperature [Min]   | 5 °C  |
| Ambient temperature [Max]   | 35 °C |
| Humity of environment [Max] | 80 %  |

| Storage temperature [Min] | -10 °C |
|---------------------------|--------|
| Storage temperature [Max] | 40 °C  |

| Approval |   |
|----------|---|
| CE mark  | ✓ |

| Services (optional)                          |         |
|--|---------|
| Article number for DAkkS calibration         | 963-101 |
| Article number for certificate of conformity | 969-517 |

| Packing & Shipping           |                |
|------------------------------|----------------|
| Delivery time                | 1 d            |
| Dimensions packaging (W×D×H) | 400×515×615 mm |
| Shipping method              | Parcel service |
| Net weight approx.           | 7 kg           |
| Gross weight approx.         | 9 kg           |
| Shipping weight              | 25,3 kg        |

### Pictograms

#### **STANDARD**



### OPTION

