# KERN CCS 60K0.1.



Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999



Category	
Brand	KERN
Product categoriy	Industrial scale
Product group	Counting system
Product family	CCS
Measuring System	
Reference scale - item number	CFS 6K0.1
Quantity scale - Item number	TKFP 60V20M-A
Construction type of the scale	Multi-range balance
Weighing system	Strain gauge
Reference scale - Weighing capacity [Max]	6 kg
Quantity scale - Weighing capacity [Max]	60 kg
Quantity scale - Readability [d]	0,002 kg
Reference scale - Readability [d]	100 mg
Reproducibility	0,0001 kg
Reference scale - Reproducibility	100 mg
Quantity scale - Reproducibility	0,002 kg
Linearity	±
Reference scale - Linearity	200 mg
Quantity scale - Linearity	0,008 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	50 kg (M1)
Stabilization time	2 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,0005 kg
Reference scale - Eccentric loading at 1/3 [Max]	500 mg
Quantity scale - Eccentric loading at 1/3 [Max]	0,01 kg
Default unit	kg
Units	kg Ib
Loadcell type	aluminum Alloy IP64

Display	
Display type	LCD
Display backlight	$\checkmark$
Display digit height	20 mm
Construction	
Dimensions completely mounted (W×D×H)	320×330×125 mm
Dimensions weighing surface (W×D)	400×300 mm
Dimensions weighing surface	400×300 mm
Dimensions weighing platform (W×D×H)	400×300×114 mm
Material housing	plastic
Material weighing plate	stainless steel
Material load cell(s)	aluminium
Level indicator	$\checkmark$
Levelling feet adjustable	$\checkmark$
Cable length	1,5 m
Display device cable length	3 m
Functions	
PreTare function	1
Sum memory function	$\checkmark$
Recipe/summing level	Sum A
Conversion function	$\checkmark$
PLU - total	100
Tolerance weighing	1
Tolerance weighing - type of signal	acoustically visual
Underfloor weighing	None
Counting function	$\checkmark$
Counting resolution (laboratory conditions)	600.000
Counting reference weight can be entered	1
Smallest piece weight when piece counting - laboratory conditions	100 mg
Smallest piece weight when piece counting - normal conditions	1 g
Reference quantity	n (any number of pieces)
IP protection - display	IP23
IP protection - platform	IP65
IP protection - load cell	IP65
Memory function	1
Auto-off interval(s) in battery mode/rechargeable battery mode	selectable
Tare function	manual (multi)

# KERN CCS 60K0.1.




Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999

Number of keys for operation	20
Interface	
Interfaces	RS-232 standard
Power Supply	
Supplied power supply Plug-in power supply type	Power supply unit Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max] Rechargeable battery	12 V, 500 mA GAB-A04
Rechargeable battery operating time - backlight on	70 h
Rechargeable battery operating time - backlight off	60 h
Rechargeable battery charging time	12 h
Rechargeable battery optional	Rchrg. battery optional
Environmental conditions	
Ambient temperature [Min]	0°C
Ambient temperature [Max]	40 °C
Humity of environment [Min]	0 %
Humity of environment [Max]	80 % -20 °C
Storage temperature [Min] Storage temperature [Max]	-20°C
Approval	
CE mark	✓
Services (optional)	
Article number for adjustment at the location of installation	abhängig von Auflösung/ Max   depends on resolution and capacity
Article number for DAkkS calibration	962-129-128
Article number for certificate of conformity (verification)	969-517

Packing & Shipping	
Delivery time	2 d
Dimensions packaging (W×D×H)	935×650×230 mm
Shipping method	Parcel service
Net weight approx.	13 kg
Gross weight approx.	17 kg
Shipping weight	28 kg

### Pictograms

### STANDARD



#### OPTION

<b>•••</b>	DAkkS
ACCU	+3 DAYS