

KERN CKE 360-3

KERN

Easy to use, self-explanatory counting scale with laboratory accuracy, counting resolution 180.000 points



Display

Display type	LCD
Display backlight	✓
Display screen size	89×30 mm
Display segments	7
Display digit height - smallest digit	20 mm
Display digit height	25 mm
Languages of the user interface	Symbol language

Construction

Dimension housing (W×D×H)	163×245×65 mm
Dimensions completely mounted (W×D×H)	163×245×123 mm
Dimensions ring-shaped draught shield - inner (Ø×H)	90×40 mm
Dimensions ring-shaped draught shield - outer (Ø×H)	106×42 mm
Dimensions weighing surface (Ø)	82 mm
Dimensions weighing surface	82 mm
Material housing	ABS plastic
Material weighing plate	plastic
Material platform	stainless steel
Material draught shield	plastic
Material display housing	plastic
Level indicator	✓
Levelling feet adjustable	✓
Transport safety lock - bolt torque	0,1 Nm

Functions

PreTare function	✓
Percentage determination	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Underfloor weighing	Hook (included in delivery)
Counting function	✓
Counting resolution (laboratory conditions)	180.000
Counting reference weight can be entered	✓
Smallest piece weight when piece counting - laboratory conditions	2 mg
Smallest piece weight when piece counting - normal conditions	20 mg
Reference quantity	5, 10, 20, n (any number of pieces)
IP protection - complete device	-

Category

Brand	KERN
Product category	Industrial scale
Product group	Counting scale
Product family	CKE

Measuring System

Weighing system	Strain gauge
Weighing capacity [Max]	360 g
Readability [d]	0,001 g
Reproducibility	0,001 g
Linearity	± 0,005 g
Resolution	360.000
Tare range	360 g

Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 g (F1)
Possible calibration points	100 g; 200 g; 350 g
Stabilization time	3 s
Eccentric loading at 1/3 [Max]	0,01 g
Construction type of the scale	Single-range balance

Units	kg
	g
	gn
	dwt
	ozt
	lb
	oz
	ffa PCS

Maximum creep (15 minutes)	10 mg
Maximum creep (30 minutes)	20 mg
Default unit	g

KERN CKE 360-3

Easy to use, self-explanatory counting scale with laboratory accuracy, counting resolution 180.000 points

Auto-off interval(s) in battery mode/rechargeable battery mode	off
	5 min
	2 min
	1 min
	30 min
	60 min

Auto-off interval(s) in mains power mode	30 sec
	off
	5 min
	2 min
	1 min
	30 min

Tare function	manual (multi)
Number of keys for operation	7

Interface

Interfaces	RS-232 (optional)
	Ethernet (optional)
	Bluetooth BLE (v4.0) (optional)
	USB-Device (optional)
	KUP
	WiFi (optional)

compatible with EasyTouch	✓
---------------------------	---

Power Supply

Supplied power supply	Power supply & battery function (battery not included)
-----------------------	--

Power supply type	Power adapter
-------------------	---------------

Plug-in power supply / adapter for countries - included with the delivery	EURO
	UK
	US
	CH

Plug-in power supply / adapter for countries - optional	EURO
	UK
	US
	CH

Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
--	---------------------------

Power supply cable removable	removable
------------------------------	-----------

Input voltage device / power [Max]	5,9V, 1A
------------------------------------	----------

Power socket for mains adapter	Hollow plug, inside minus, Ø inside 2,1 mm,
	Ø outside 5,5 mm, long 12 mm

Battery / accumulator type	Li-Ion
----------------------------	--------

Battery	4×1.5 V AA
---------	------------

Battery connection	Battery insert
--------------------	----------------

Battery operating time	20 h
------------------------	------

Rechargeable battery operating time - backlight on	24 h
--	------

Rechargeable battery operating time - backlight off	48 h
---	------

Rechargeable battery charging time	8 h
------------------------------------	-----

Rechargeable battery optional	Rchrg. battery optional
-------------------------------	-------------------------

Environmental conditions

Ambient temperature [Min]	-10 °C
---------------------------	--------

Ambient temperature [Max]	40 °C
---------------------------	-------

Humidity of environment [Max]	80 %
-------------------------------	------

Approval

CE mark	✓
---------	---

Services (optional)

Article number for DAkKS calibration	963-127
--------------------------------------	---------

Article number for certificate of conformity	969-517
--	---------

Packing & Shipping

Delivery time	1 d
---------------	-----

Dimensions packaging (W×D×H)	235×365×175 mm
------------------------------	----------------

Shipping method	Parcel service
-----------------	----------------

Net weight approx.	0,85 kg
--------------------	---------

Gross weight approx.	1,8 kg
----------------------	--------

Shipping weight	3 kg
-----------------	------

Product information


GTIN/EAN number	4045761243439
-----------------	---------------

Trade number	90160010
--------------	----------

REACH classification	no prohibited substances
----------------------	--------------------------

Pictograms

STANDARD



OPTION

