

# KERN EG 2200-2NM

**KERN**

The classic balance with robust tuning fork measuring system



Category	
Brand	KERN
Product category	Laboratory balance
Product group	Precision balance
Product family	EG

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Tuning fork
Weighing capacity [Max]	2200 g
Weighing capacity [Max] (ct)	11000 ct
Readability [d]	0,01 g
Readability carat [d] (ct)	0,1 ct
Reproducibility	0,01 g
Linearity	± 0,01 g
USP Minimum weight of sample (k = 2, U = 0.1%)	20 g
Minimum weight [Min]	0,5 g
Minimum weight [Min] (ct)	5 ct
Resolution	220.000
Adjustment options	Adjusting with internal weight (manual)
Stabilization time	3 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,03 g
Default unit	g

Units

g  
dw  
tl (Tw)  
tl (HK)  
ozt  
tl (Singap, Malays)  
ct

mo  
lb  
oz  
tol

Units (if device is conformity assessed)	g ct
Conformity assessment possible	✓

Display	
Display type	LCD
Display backlight	✓
Display screen size	109×22 mm
Display digit height	17 mm
Languages of the user interface	Symbol language

Construction	
Dimension housing (W×D×H)	180×235×75 mm
Dimensions completely mounted (W×D×H)	180×235×75 mm
Dimensions weighing surface (W×D)	180×160 mm
Dimensions weighing surface	180×160 mm
Material housing	plastic
Material weighing plate	stainless steel
Material platform	stainless steel
Level indicator	✓
Levelling feet adjustable	✓

Functions	
Percentage determination	✓
Tolerance weighing	✓
Underfloor weighing	Eye (optional)
Capacity - Display	✓
Counting function	✓
Counting resolution (laboratory conditions)	220.000
Smallest piece weight when piece counting - laboratory conditions	10 mg
Smallest piece weight when piece counting - normal conditions	100 mg
Reference quantity	10, 30, 50, 100
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min
Auto-off interval(s) in mains power mode	3 min
Tare function	manual (multi)
Number of keys for operation	5

# KERN EG 2200-2NM



The classic balance with robust tuning fork measuring system

Interface	
Interfaces	RS-232 standard

Power Supply	
Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH

Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max]	12 V, 1 A
Battery / accumulator type	NiCd
Rechargeable battery	EG-A06
Rechargeable battery operating time - backlight on	12 h
Rechargeable battery charging time	12 h
Rechargeable battery optional	Rchrg. battery optional

Environmental conditions	
Ambient temperature [Min]	10 °C
Ambient temperature [Max]	30 °C
Humidity of environment [Max]	80 %

Approval	
CE mark	✓
Conformity assessment possible ex works	✓
Accuracy classe	II
Verification scale interval [e]	0,1 g
Verification scale interval [e] (ct)	1 ct

Services (optional)	
Article number for conformity assessment	965-216
Article number for DAkkS calibration	963-127
Article number for certificate of conformity	969-517

Packing & Shipping	
Delivery time	1 d

Dimensions packaging (W×D×H)	325×410×220 mm
Shipping method	Parcel service
Net weight approx.	4,0 kg
Gross weight approx.	6 kg
Shipping weight	5,9 kg

## Pictograms

### STANDARD



### OPTION



### FACTORY

