KERN FCF 3K-4



Compact bench scale with multi-purpose functionality and a high level of accuracy for use in industry, gastronomy and kitchen



Category	
Brand	KERN
Product categoriy	Industrial scale
Product group	Bench scale
Product family	FCF
Measuring System	

Single-range balance
Strain gauge
1
3000 g
0,1 g
0,1 g
± 0,3 g
30.000
3000 g
Adjusting with external weight
2 kg (M1); 1 kg (M1)
1 kg; 2 kg; 3 kg
3 s
120 min
0,3 g
400 mg
800 mg
g
g dwt tl (Tw) tl (HK) ozt mo lb

	oz tol
Display	
Display type Display digit height	LCD 25 mm
Construction	
Dimension housing (W×D×H)	270×345×106 mm
Dimensions completely mounted (W×D×H)	270×345×106 mm
Dimensions weighing surface (W×D)	253×228 mm
Dimensions weighing surface	253×228 mm
Material housing	plastic
Material weighing plate	stainless steel
Level indicator	✓
Functions	
Recipe/summing level	Rez A (Net total)
Percentage determination	1
Underfloor weighing	None
Function for averaging under unstable weighing conditions	1
Counting function	1
Counting resolution (laboratory conditions)	15.000
Smallest piece weight when piece counting - laboratory conditions	200 mg
Smallest piece weight when piece counting - normal conditions	2 g
Reference quantity	5, 10, 20, 25, 50
IP protection - complete device	-
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min
Auto-off interval(s) in mains power mode	3 min
Tare function	manual (multi)
Number of keys for operation	5
Power Supply	
Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz

KERN FCF 3K-4



Compact bench scale with multi-purpose functionality and a high level of accuracy for use in industry, gastronomy and kitchen

Input voltage device / power [Max]	9 V, 300 mA
Battery / accumulator type	Alkali(-Manganese)
Battery	9 V block
Battery connection	Pad + Spring
Battery operating time	20 h
Rechargeable battery operating time - backlight on	80 h
Rechargeable battery operating time - backlight off	120 h
Rechargeable battery charging time	16 h
Rechargeable battery optional	Rchrg. battery optional - intern

Environmental conditions

1

Approval

CE mark

Services (optional)

Article number for adjustment at the location of installation	961-247
Article number for DAkkS calibration	963-127
Article number for certificate of conformity	969-517

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	335×400×185 mm
Shipping method	Parcel service
Net weight approx.	2,8 kg
Gross weight approx.	3,4 kg
Shipping weight	5 kg

Pictograms

STANDARD





1 DAY

OPTION

