

# KERN FFN 1K-4N

**KERN**

All-round bench scale, protected by stainless steel and IP65 rating



## Category

Brand	KERN
Product category	Industrial scale
Product group	IP protected bench scale
Product family	FFN

## Measuring System

Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Number of weighing ranges	1
Weighing capacity [Max]	1,5 kg
Readability [d]	0,0002 kg
Reproducibility	0,0002 kg
Linearity	± 0,0004 kg
Resolution	7.500
Tare range	-1,5 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	1,5 kg (M1)
Possible calibration points	1,5 kg
Stabilization time	2 s
Warm-up time	30 min
Eccentric loading at 1/3 [Max]	0,001 kg
Maximum creep (15 minutes)	800 mg
Maximum creep (30 minutes)	1,6 g
Default unit	kg
Units	kg lb
Loadcell type	aluminium IP65 silicone-coated

## Display

Display type	LCD
Display backlight	✓
Display segments	5
Display digit height	25 mm

## Construction

Dimension housing (W×D×H)	243×300×127 mm
Dimensions completely mounted (W×D×H)	243×300×127 mm
Dimensions weighing surface (W×D)	233×193 mm
Dimensions weighing surface	233×193 mm
Material housing	stainless steel, plastic
Material weighing plate	stainless steel
Material load cell(s)	aluminium
Level indicator	✓
Levelling feet adjustable	✓

## Functions

Underfloor weighing	None
IP protection - complete device	IP65
Auto-off interval(s) in mains power mode	3 min off 5 min 15 min
Tare function	manual (multi)
Number of keys for operation	3

## Power Supply

Supplied power supply	Accu & Power supply
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Input voltage power supply / power [Max]	110 V - 230 V AC
Input voltage device / power [Max]	12 V, 500 mA
Battery / accumulator type	Pb
Battery	no battery
Battery connection	Plug-in terminals
Rechargeable battery	WTB-A01N

# KERN FFN 1K-4N



All-round bench scale, protected by stainless steel and IP65 rating

Rechargeable battery operating time - backlight on	30 h
--	------

Rechargeable battery operating time - backlight off	50 h
---	------

Rechargeable battery charging time	12 h
------------------------------------	------

## Environmental conditions

Ambient temperature [Min]	-10 °C
---------------------------	--------

Ambient temperature [Max]	40 °C
---------------------------	-------

Humidity of environment [Min]	25 %
-------------------------------	------

Humidity of environment [Max]	95 %
-------------------------------	------

Storage temperature [Min]	-20 °C
---------------------------	--------

Storage temperature [Max]	60 °C
---------------------------	-------

## Approval

CE mark	✓
---------	---

## Services (optional)

Article number for adjustment at the location of installation	961-247
---	---------

Article number for DAkkS calibration	963-127
--------------------------------------	---------

Article number for certificate of conformity	969-517
--	---------

## Packing & Shipping

Delivery time	1 d
---------------	-----

Dimensions packaging (W×D×H)	310×402×205 mm
------------------------------	----------------

Shipping method	Parcel service
-----------------	----------------

Net weight approx.	4,0 kg
--------------------	--------

Gross weight approx.	4,6 kg
----------------------	--------

Shipping weight	5,1 kg
-----------------	--------

## Pictograms

### STANDARD



### OPTION

