KERN FH 100K



Universal digital force gauge for tensile and compressive force measurements with external load cell



Category	
Brand	Sauter
Product categoriy	Force measurement
Product group	Digital force gauge (external measuring cell)
Product family	FH-M
Measuring System	
Measuring range force [Max] (N)	100 kN
Readability force [d] (N)	50 N
Measuring head measuring frequency	2 kHz
Overload protection (% of [Max])	150%
Default unit	kN
Internal data memory: Number of individual values	10
Internal data memory: Number of value groups	1
Number of platforms / channels	1
Tolerance (% of [Max])	0,5%
Directions of force	tension compression
Display	

D	IS	рі	а	y	

Display type	LCD
Display digit height	10 mm
Screen reversible	\checkmark

Construction

Dimension housing (W×D×H) Dimensions completely mounted (W×D×H)

230×66×36 mm 365×325×155 mm

N	
Dimension display device (W×D×H)	230×66×36 mm
Dimensions load cell	178×125×51 mm
Material display housing	Plastics
Cable length	3 m
Mounting - force dissipation	Threaded hole M30 × 2
Mounting - force application	Threaded hole M30 \times 2
Load support (tensile force)	Rod end
Functions	
Function for averaging	1
Limit-setting function	✓
Hold function	1
Peak function	· /
Memory function	✓ ✓
Statistic function	√ √
	V
Auto-off interval(s) in battery mode/rechargeable battery mode	1 - 60 min
Interface	
Interfaces	RS-232 standard
Power Supply	
Supplied power supply	Accu & Power supply
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for	
countries - included with the	EURO CH
delivery	OII
Plug-in power supply / adapter for countries - optional	UK US
Input voltage power supply / power [Max]	100 V - 240 V
Input voltage device / power [Max]	12 V, 400 mA
Battery / accumulator type	NIMH
Rechargeable battery	8,4V / 1200mAh Ni-Hi
Rechargeable battery operating	
time - backlight on	10 h
Rechargeable battery operating time - backlight off	12 h
Rechargeable battery charging	
time	4 h
	
Environmental conditions	
Ambient temperature [Min]	10 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-10 °C
Storage temperature [Max]	40 °C

KERN FH 100K



Universal digital force gauge for tensile and compressive force measurements with external load cell

Approval	
CE mark	\checkmark
Services (optional)	
Article number for factory calibration (tensile force)	961-166
Article number for factory calibration (compressive force)	961-266
Article number for factory calibration (tensile force/ compressive force)	961-366
Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	325×185×165 mm
Shipping method	Parcel service
Net weight approx.	11 kg

D	at	0	ar	- 01	\sim	
Pi	Cι	υ	۲I	a		5

Shipping weight

Gross weight approx.

STANDARD



12 kg

11,3 kg



OPTION

