KERN FKB 15K0.5



High resolution bench scale with large weighing range and robust stainless steel weighing plate



Category			
Brand	KERN		
Product categoriy	Industrial scale		
Product group	Bench scale		
Product family	FKB		
Moneuring System			

Measuring	System

Construction type of the scale	Single-range balance			
Weighing system	Strain gauge			
Weighing capacity [Max]	15 kg			
Readability [d]	0,0005 kg			
Reproducibility	0,0005 kg			
Linearity	± 0,0015 kg			
Resolution	30.000			
Adjustment options	Adjusting with external weight			
Recommended adjusting weight	15 kg (F2)			
Possible calibration points	5 kg; 10 kg; 15 kg			
Stabilization time	3 s			
Warm-up time	120 min			
Eccentric loading at 1/3 [Max]	0,0025 kg			
Maximum creep (15 minutes)	2 g			
Maximum creep (30 minutes)	4 g			
Default unit	kg			
	kg g gn dwt ozt			
Units	lb oz ffa PCS %			

Display			
Display type	LCD		
Display backlight	✓		
Display screen size	120×38 mm		
Display digit height	25 mm		
Languages of the user interface	English Symbol language		
Construction			
Dimension housing (W×D×H)	350×390×120 mm		
Dimensions weighing surface (W×D)	340×240 mm		
Dimensions weighing surface	340×240 mm		
Dimensions weighing platform (W×D×H)	340×240×21 mm		
Material housing	ABS plastic		
Material weighing plate	stainless steel		
Material display housing	plastic		
Level indicator	\checkmark		
Levelling feet adjustable	1		
Functions			
Recipe/summing level	Sum A		
Percentage determination	1		
Tolerance weighing	1		
Tolerance weighing - type of signal	acoustically visual		
Underfloor weighing	Hook (included in delivery)		
Function for averaging under unstable weighing conditions	1		
Counting function	\checkmark		
Counting resolution (laboratory conditions)	15.000		
Counting reference weight can be entered	1		
Smallest piece weight when piece counting - laboratory conditions	1 g		
Smallest piece weight when piece counting - normal conditions	10 g		
Reference quantity	5, 10, 20, 50, n (any number of pieces)		
IP protection - display	no IP protection		
Auto-off interval(s) in battery mode/rechargeable battery mode	5 min 2 min 1 min 30 min 60 min 30 sec		

KERN FKB 15K0.5



High resolution bench scale with large weighing range and robust stainless steel weighing plate

Auto-off interval(s) in mains power mode	off			
Tare function	manual (multi)			
Number of keys for operation	6			
Interface				
Interfaces	RS-232 (optional) Ethernet (optional) Bluetooth BLE (v4.0) (optional) USB-Device (optional) KUP WiFi (optional)			
compatible with EasyTouch	\checkmark			
Power Supply				
Supplied power supply	Power supply unit			
Plug-in power supply type	Power adapter			
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH			
Plug-in power supply / adapter for countries - optional	EURO UK US CH			
Input voltage power supply / power [Max]	100 V - 240 V AC, 50 / 60 Hz			
Input voltage device / power [Max]	5,9V, 1A			
Battery / accumulator type	Li-Ion			
Battery	4×1.5 V AA			
Battery connection	Battery insert			
Battery operating time	20 h			
Rechargeable battery operating time - backlight on	24 h			
Rechargeable battery operating time - backlight off	48 h			
Rechargeable battery charging time	8 h			
Rechargeable battery optional	Rchrg. battery optional - intern			
Environmental conditions				

Environmental conditions				
Ambient temperature [Min]	-10 °C			
Ambient temperature [Max]	40 °C			
Humity of environment [Max]	80 %			
Storage temperature [Min]	-20 °C			
Storage temperature [Max]	60 °C			

Approval				
CE mark	✓			
Services (optional)				
Article number for adjustment at the location of installation	961-248			
Article number for DAkkS calibration	963-128			
Article number for certificate of conformity	969-517			
Packing & Shipping				
Delivery time	1 d			
Dimensions packaging (W×D×H)	470×470×190 mm			
Shipping method	Parcel service			
Net weight approx.	7 kg			
Gross weight approx.	6 kg			
Shipping weight	8,4 kg			

Pictograms

STANDARD



OPTION

1	- 888. •	•	(((-	୲ୡ	<u>–</u>	••	DAkkS
ET	RS 232	USB	WIFI	BT 4.0	LAN	ACCU	+3 DAYS