# KERN FKB 16K0.05



High resolution bench scale with large weighing range and robust stainless steel weighing plate



Category			
Brand	KERN		
Product categoriy	Industrial scale		
Product group	Bench scale FKB		
Product family			
Measuring System			
Construction type of the scale	Single-range balance		
Weighing system	Strain gauge		
Weighing capacity [Max]	16 kg		
Readability [d]	0,00005 kg		
Reproducibility	0,0001 kg		
Linearity	± 0,00025 kg		
Resolution	320.000		
Adjustment options	Adjusting with external weight 10 kg (F1); 5 kg (F1); 1 kg (F1)		
Recommended adjusting weight			
Possible calibration points	5 kg; 10 kg; 15 kg		
Stabilization time	3 s		
Warm-up time	120 min		
Eccentric loading at 1/3 [Max]	0,00025 kg		
Maximum creep (15 minutes)	500 mg		
Maximum creep (30 minutes)	1 g		
Default unit	kg		
Units	kg g gn dwt ozt Ib oz		
	ffa		

	PCS %			
Display				
Display type	LCD			
Display backlight	✓			
Display screen size	120×38 mm			
Display digit height	25 mm English Symbol language			
Languages of the user interface				
Construction				
Dimension housing (W×D×H)	350×390×120 mm			
Dimensions weighing surface (W×D)	340×240 mm			
Dimensions weighing surface	340×240 mm			
Dimensions weighing platform (W×D×H)	340×240×21 mm			
Material housing	ABS plastic			
Material weighing plate	stainless steel			
Material display housing	plastic			
Level indicator	$\checkmark$			
Levelling feet adjustable	1			
Functions				
Recipe/summing level	Sum A			
Percentage determination	✓			
Conversion function	✓			
Tolerance weighing	$\checkmark$			
Tolerance weighing - type of signal	acoustically visual			
Underfloor weighing	Hook (included in delivery)			
Function for averaging under unstable weighing conditions	1			
Counting function	$\checkmark$			
Counting resolution (laboratory conditions)	320.000			
Counting reference weight can be entered	1			
Smallest piece weight when piece counting - laboratory conditions	50 mg			
Smallest piece weight when piece counting - normal conditions	500 mg			
Reference quantity	5, 10, 20, 50, n (any number of pieces)			
Reference quantity				
IP protection - display				
	number of pieces)			

## KERN FKB 16K0.05



High resolution bench scale with large weighing range and robust stainless steel weighing plate

	1 min 30 min 60 min 30 sec
Auto-off interval(s) in mains power mode	off
Tare function	manual (multi)
Number of keys for operation	6

Interface	
Interfaces	RS-232 (optional) Ethernet (optional) Bluetooth BLE (v4.0) (optional) USB-Device (optional) KUP WiFi (optional)
compatible with EasyTouch	$\checkmark$

compatible with EasyTouch

Ambient temperature [Max] Humity of environment [Max]

### Power Supply

Fower Supply				
Supplied power supply	Power supply unit			
Plug-in power supply type	Power adapter			
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH			
Plug-in power supply / adapter for countries - optional	EURO UK US CH			
Input voltage power supply / power [Max]	100 V - 240 V AC, 50 / 60 Hz			
Input voltage device / power [Max]	5,9V, 1A			
Battery / accumulator type	Li-Ion			
Battery	4×1.5 V AA			
Battery connection	Battery insert			
Battery operating time	20 h			
Rechargeable battery operating time - backlight on	24 h			
Rechargeable battery operating time - backlight off	48 h			
Rechargeable battery charging time	8 h			
Rechargeable battery optional	Rchrg. battery optional - intern			
Environmental conditions				
Ambient temperature [Min]	-10 °C			

40 °C

80 %

Storage temperature [Min]	-20 °C			
Storage temperature [Max]	60 °C			
Approval				
CE mark	1			
Services (optional)				
Article number for DAkkS calibration	963-128			
Article number for certificate of conformity	969-517			
Packing & Shipping				
Delivery time	1 d			
Dimensions packaging (W×D×H)	470×470×190 mm			
Shipping method	Parcel service			
Net weight approx.	7 kg			
Gross weight approx.	8 kg			
Shipping weight	8,4 kg			

### Pictograms

#### **STANDARD**



#### **OPTION**

1		•	(((•	*	臺	<b>•••</b>	DAkkS
ET	RS 232	USB	WIFI	BT 4.0	LAN	ACCU	+3 DAYS