KERN FKB 36K0.1



High resolution bench scale with large weighing range and robust stainless steel weighing plate



Category	
Brand	KERN
Product categoriy	Industrial scale
Product group	Bench scale
Product family	FKB

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	36 kg
Readability [d]	0,0001 kg
Reproducibility	0,0002 kg
Linearity	± 0,0005 kg
Resolution	360.000
Adjustment options	Adjusting with external weight
Recommended adjusting weight	20 kg (E2); 10 kg (E2)
Possible calibration points	10 kg; 20 kg; 30 kg
Stabilization time	3 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,0005 kg
Maximum creep (15 minutes)	1 g
Maximum creep (30 minutes)	2 g
Default unit	kg
Units	kg g gn dwt ozt lb oz ffa PCS %

Display	
Display type	LCD
Display backlight	✓
Display screen size	120×38 mm
Display digit height	25 mm
Languages of the user interface	English Symbol language

Construction	
Dimension housing (W×D×H)	350×390×120 mm
Dimensions weighing surface (W×D)	340×240 mm
Dimensions weighing surface	340×240 mm
Dimensions weighing platform (W×D×H)	340×240×21 mm
Material housing	ABS plastic
Material weighing plate	stainless steel
Material display housing	plastic
Level indicator	✓
Levelling feet adjustable	✓

Functions	
Recipe/summing level	Sum A
Percentage determination	✓
Conversion function	✓
Tolerance weighing	\checkmark
Tolerance weighing - type of signal	acoustically visual
Underfloor weighing	Hook (included in delivery)
Function for averaging under unstable weighing conditions	✓
Counting function	✓
Counting resolution (laboratory conditions)	360.000
Counting reference weight can be entered	1
Smallest piece weight when piece counting - laboratory conditions	100 mg
Smallest piece weight when piece counting - normal conditions	1 g
Reference quantity	5, 10, 20, 50, n (any number of pieces)
IP protection - display	no IP protection
Auto-off interval(s) in battery mode/rechargeable battery mode	5 min 2 min 1 min 30 min

1

KERN FKB 36K0.1



190 mm

DAkkS +3 DAYS

High resolution bench scale with large weighing range and robust stainless steel weighing plate

	60 min 30 sec
Auto-off interval(s) in mains power mode	off
Tare function	manual (multi)
Number of keys for operation	6

Interface	
Interfaces	RS-232 (optional) Ethernet (optional) Bluetooth BLE (v4.0) (optional) USB-Device (optional) KUP WiFi (optional)
compatible with EasyTouch	✓

Power Supply	
Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Input voltage power supply / power [Max]	100 V - 240 V AC, 50 / 60 Hz
Input voltage device / power [Max]	5,9V, 1A
Battery / accumulator type	Li-lon
Battery	4×1.5 V AA
Battery connection	Battery insert
Battery operating time	20 h
Rechargeable battery operating time - backlight on	24 h
Rechargeable battery operating time - backlight off	48 h
Rechargeable battery charging time	8 h
Rechargeable battery optional	Rchrg. battery optional - intern

-10 °C

40 °C

80 %

-20 °C 60 °C

Environmental conditions

Ambient temperature [Min]

Ambient temperature [Max]

Storage temperature [Min]

Storage temperature [Max]

Humity of environment [Max]

Thhio	val				
CE mar	k			✓	
Servic	es (optior	nal)			
Article calibra	number for ion	DAkkS		963-	128
Article confor	number for nity	certificat	e of	969-	517
Packii	ng & Shipp	oing			
Deliver	y time			1 d	
	, sions packaį	ging (W×[D×H)	470×	470×1
	g method		,	Parce	el servi
	ight approx.			7 kg	
	veight appro			8 kg	
	g weight			8,4 k	g
CAL EXT	KCP KUP PROTOCO	PRINTER	PCS	SUM	% PERCENT
MOVE	UNDER BATT	MULTI	DMS	1 DAY	
OPTION					