## KERN FS 2-100KRY1



Ready-assembled set consisting of premium force gauge FS 2 and load cell CR 10000-1Y1 for tensile and compressive force measurements



| Category                              |   |
|---------------------------------------|---|
| Brand                                 | Sauter  |
| Product categoriy                     | Force measurement                                 |
| Product group                         | Force measuring device set                        |
| Product family                        | FS RY1  |
| Measuring System                      |   |
| Measuring range force [Max] (N)       | 100 kN  |
| Readability force [d] (N)             | 20 N  |
| Measuring head measuring<br>frequency | 1000 Hz   |
| Default unit                          | Ν   |
| Number of platforms / channels        | 2   |
| Directions of force                   | tension<br>compression                            |
| Display                               |   |
| Display type                          | TFT, color  |
| Display resolution                    | 320×480   |
| Languages of the user interface       | German<br>English<br>French<br>Spanish<br>Italian |
| Construction                          |   |
| Dimensions load cell (cylindrical)    | 125×52 mm   |
| Material housing                      | plastic   |
| Material display housing              | Plastics  |

Mounting - force dissipation

Mounting - force application

8 × through hole Ø 8,5

Threaded hole M32  $\times$  1,5

mm

| Functions   |                               |
|---|-------------------------------|
| IP protection - load cell   | IP68                          |
| Peak function   | 1                             |
| Memory function   | 1                             |
| Statistic function  | $\checkmark$                  |
| Auto-off interval(s) in battery mode/rechargeable battery mode                  | selectable                    |
| Interface   |                               |
| Interfaces  | USB-Device                    |
| Power Supply  |                               |
| Supplied power supply   | Accu & Power supply           |
| Plug-in power supply type   | USB including power<br>supply |
| Plug-in power supply / adapter for<br>countries - included with the<br>delivery | EURO                          |
| Plug-in power supply / adapter for countries - optional                         | UK                            |
| Input voltage power supply /<br>power [Max]                                     | 100 V - 240 V, 50 / 60<br>Hz  |
| Input voltage device / power [Max]  | 5 V, 1 A                      |
| Battery / accumulator type  | Li-Ion                        |
| Battery connection  | 2-pole tub connector          |
| Battery capacity  | 2.400 mAh                     |
| Battery voltage   | 3,7 V                         |
| Rechargeable battery  | 3,7V, 2400mAh                 |
| Rechargeable battery operating time - backlight on                              | 5 h                           |
| Rechargeable battery operating time - backlight off                             | 8 h                           |
| Rechargeable battery charging time  | 8 h                           |
| Approval  |                               |
| CE mark   | 1                             |
| Services (optional)   |                               |
| Article number for factory<br>calibration (tensile force)                       | 961-166                       |
| Article number for factory<br>calibration (compressive force)                   | 961-266                       |
| Article number for factory<br>calibration (tensile force/<br>compressive force) | 961-366                       |
| . ,   |                               |

## KERN FS 2-100KRY1



Ready-assembled set consisting of premium force gauge FS 2 and load cell CR 10000-1Y1 for tensile and compressive force measurements

## Packing & Shipping

| Delivery time        | 3 d            |
|----------------------|----------------|
| Shipping method      | Parcel service |
| Net weight approx.   | 2,0 kg         |
| Gross weight approx. | 3,0 kg         |
| Shipping weight      | 2,985 kg       |

## Pictograms

**STANDARD** 



OPTION

