KERN FS 2-10KSP1



Ready-assembled set consisting of premium force gauge FS 2 and external "S" measuring cell CS 1000-3P1 for tensile and compressive force measurements



Category	
Brand	Sauter
Product categoriy	Force measurement
Product group	Force measuring device set
Product family	FS SP1
Measuring System	
Measuring range force [Max] (N)	10 kN
Readability force [d] (N)	2 N
Measuring head measuring frequency	1000 Hz
Default unit	Ν
Number of platforms / channels	2
Directions of force	tension compression
Display	
Display type	TFT, color
Display resolution	320×480
Languages of the user interface	German English French Spanish Italian
Construction	
Dimensions load cell	50,8×76,2×25,4 mm
Material housing	plastic

Plastics

Threaded hole M12

Threaded hole M12

Material display housing

Mounting - force dissipation

Mounting - force application

Functions	
IP protection - load cell	IP67
Peak function	\checkmark
Memory function	\checkmark
Statistic function	\checkmark
Auto-off interval(s) in battery mode/rechargeable battery mode	selectable
Interface	
Interfaces	USB-Device
Power Supply	
Supplied power supply	Accu & Power supply
Plug-in power supply type	USB including power supply
Plug-in power supply / adapter for countries - included with the delivery	EURO
Plug-in power supply / adapter for countries - optional	UK
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	5 V, 1 A
Battery / accumulator type	Li-Ion
Battery connection	2-pole tub connector
Battery capacity	2.400 mAh
Battery voltage	3,7 V
Rechargeable battery	3,7V, 2400mAh
Rechargeable battery operating time - backlight on	5 h
Rechargeable battery operating time - backlight off	8 h
Rechargeable battery charging time	8 h
Approval	
CE mark	✓
Services (optional)	
Article number for factory calibration (tensile force)	961-164
Article number for factory calibration (compressive force)	961-264
Article number for factory calibration (tensile force/ compressive force)	961-364

KERN FS 2-10KSP1



Ready-assembled set consisting of premium force gauge FS 2 and external "S" measuring cell CS 1000-3P1 for tensile and compressive force measurements

Packing & Shipping

Delivery time	3 d
Shipping method	Parcel service
Net weight approx.	1,00 kg
Gross weight approx.	2,0 kg
Shipping weight	1,91 kg

Pictograms

STANDARD



OPTION

