

# KERN HFC 10T-3



Compact crane scale for use in harsh environmental conditions or where space is limited, with convenient hand-held terminal



## Category

Brand	KERN
Product category	Industrial scale
Product group	Crane scale
Product family	HFC

## Measuring System

Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	10000 kg
Readability [d]	5 kg
Reproducibility	5 kg
Linearity	± 10 kg
Resolution	2.000
Adjustment options	Adjusting with external weight
Recommended adjusting weight	10000 kg (M3)
Possible calibration points	10000 kg
Stabilization time	2 s
Warm-up time	10 min
Maximum creep (15 minutes)	10 kg
Maximum creep (30 minutes)	20 kg
Eccentric/Off-centre loading is not possible	✓
Default unit	kg
Units	kg lb N
Internal measuring frequency	10 Hz
Tolerance (% of [Max])	0,2%
Loadcell type	stainless steel silicone-coated

## Display

Display type	LCD
Display type	LCD with backlight

Display backlight	✓
Display digit height	23 mm
Languages of the user interface	English Symbol language

## Construction

Dimension housing (W×D×H)	90×71,6×275 mm
Dimension display device (W×D×H)	85×64×256 mm
Dimensions housing - width (A)	90 mm
Dimensions housing - depth (B)	72 mm
Dimensions housing - height/length (C)	100 mm
Dimensions - total height/total length (D)	275 mm
Dimensions - inner length (E)	185 mm
Dimensions loop/top - hole diameter (F)	40 mm
Dimensions hook/bottom - hole diameter (G)	40 mm
Dimensions loop/top - thickness (H)	40 mm
Dimensions hook/bottom - thickness (I)	40 mm
Material housing	steel
Material load hook	steel
Material display housing	metal
Material load cell(s)	stainless steel
Load cells - number	1

## Functions

Sum memory function	✓
Recipe/summing level	Sum A
Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Underfloor weighing	None
Capacity - Display	✓
Range of radio module	20 m
Hold function	✓
Peak function	✓
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min 5 min 30 min 15 min
Auto-off interval(s) in mains power mode	5 min 30 min 15 min
Tare function	manual (multi)
Number of keys for operation	8

# KERN HFC 10T-3



Compact crane scale for use in harsh environmental conditions or where space is limited, with convenient hand-held terminal

## Power Supply

Supplied power supply	Accu & Power supply
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	9 V, 800 mA
Battery / accumulator type	NiMH
Battery	3×1.5 V AA
Battery connection	Pad + Spring
Battery operating time	40 h
Battery capacity	1.800 mAh
Battery voltage	3,6 V
Rechargeable battery	HFA-A01
Rechargeable battery operating time - backlight on	15 h
Rechargeable battery operating time - backlight off	30 h
Rechargeable battery charging time	12 h

## Environmental conditions

Ambient temperature [Min]	5 °C
Ambient temperature [Max]	35 °C
Humidity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

## Approval

CE mark	✓
TÜV-tested	✓

## Services (optional)

Article number for adjustment at the location of installation	961-252
Article number for DAkkS calibration	963-133H
Article number for certificate of conformity	969-517

## Packing & Shipping

Delivery time	1 d
---------------	-----

Dimensions packaging (W×D×H) 505×405×120 mm

Shipping method Parcel service

Net weight approx. 6 kg

Gross weight approx. 8 kg

Shipping weight 7,4 kg

## Pictograms

### STANDARD



### OPTION

