## KERN MBC 15K2DEM



Elegantly-shaped baby scale – with approval for professional mobile or stationary medical use in medical diagnostics, verification optional



#### Category

Brand Product categoriy Product group Product family KERN Medical scale Baby scale MBC

#### Measuring System

0,	
Construction type of the scale	Multi-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	6 kg; 15 kg
Readability [d]	0,002 kg; 0,005 kg
Reproducibility	0,002 kg; 0,005 kg
Linearity	± 0,002 kg; 0,005 kg
Minimum weight [Min]	0,04 kg; 0,1 kg
Resolution	3.000, 3.000
Tare range	6 kg; 14,995 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	15 kg (M1)
Stabilization time	3 s
Warm-up time	10 min; 10 min
Eccentric loading at 1/3 [Max]	0,002 kg
Default unit	kg
Units	kg
Conformity assessment possible	1

### Display

Diopiay	
Display type	LCD
Display backlight	<b>√</b>
Display digit height	25 mm
Languages of the user interface	Symbol language

#### Construction

Dimension housing (W×D×H)

320×410×70 mm

Dimensions completely mounted (W×D×H)	600×407×120 mm
Dimension display device (W×D×H)	200×130×60 mm
Dimensions weighing surface (W×D)	600×280 mm
Dimensions weighing surface	600×280 mm
Dimensions weighing platform (W×D×H)	600×280×55 mm
Material housing	plastic
Material weighing plate	plastic
Material platform	Plastics
Material display housing	Plastics
Level indicator	$\checkmark$
Functions	
Function for averaging under unstable weighing conditions	1
Hold function	✓
	3 min
Auto-off interval(s) in battery	5 min
mode/rechargeable battery mode	30 min 15 min
Tare function	manual (single & multi)
Number of keys for operation	6
······································	
Power Supply	
Power Supply Supplied power supply	Battery
	Battery Power adapter
Supplied power supply	-
Supplied power supply Plug-in power supply type Input voltage power supply /	Power adapter 100 V - 240 V, 50 / 60
Supplied power supply Plug-in power supply type Input voltage power supply / power [Max]	Power adapter 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese)
Supplied power supply Plug-in power supply type Input voltage power supply / power [Max] Input voltage device / power [Max] Battery / accumulator type Battery	Power adapter 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA
Supplied power supply Plug-in power supply type Input voltage power supply / power [Max] Input voltage device / power [Max] Battery / accumulator type Battery Battery connection	Power adapter 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA Battery insert
Supplied power supply Plug-in power supply type Input voltage power supply / power [Max] Input voltage device / power [Max] Battery / accumulator type Battery Battery connection Battery operating time	Power adapter 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA Battery insert 20 h
Supplied power supply Plug-in power supply type Input voltage power supply / power [Max] Input voltage device / power [Max] Battery / accumulator type Battery Battery connection Battery operating time Battery voltage	Power adapter 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA Battery insert 20 h 9 V
Supplied power supply Plug-in power supply type Input voltage power supply / power [Max] Input voltage device / power [Max] Battery / accumulator type Battery Battery connection Battery operating time Battery voltage Rechargeable battery	Power adapter 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA Battery insert 20 h
Supplied power supply Plug-in power supply type Input voltage power supply / power [Max] Input voltage device / power [Max] Battery / accumulator type Battery accumulator type Battery connection Battery operating time Battery voltage Rechargeable battery Rechargeable battery operating time - backlight on	Power adapter 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA Battery insert 20 h 9 V
Supplied power supply Plug-in power supply type Input voltage power supply / power [Max] Input voltage device / power [Max] Battery / accumulator type Battery / accumulator type Battery operating time Battery operating time Battery voltage Rechargeable battery Rechargeable battery operating time - backlight on	Power adapter 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA Battery insert 20 h 9 V MBC-A08
Supplied power supply Plug-in power supply type Input voltage power supply / power [Max] Input voltage device / power [Max] Battery / accumulator type Battery accumulator type Battery connection Battery operating time Battery voltage Rechargeable battery Rechargeable battery operating time - backlight on Rechargeable battery operating	Power adapter 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA Battery insert 20 h 9 V MBC-A08 20 h
Supplied power supply Plug-in power supply type Input voltage power supply / power [Max] Input voltage device / power [Max] Battery / accumulator type Battery accumulator type Battery connection Battery operating time Battery voltage Rechargeable battery Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off Rechargeable battery charging	Power adapter 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA Battery insert 20 h 9 V MBC-A08 20 h 40 h
Supplied power supply Plug-in power supply type Input voltage power supply / power [Max] Input voltage device / power [Max] Battery / accumulator type Battery accumulator type Battery operating time Battery operating time Battery voltage Rechargeable battery Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off Rechargeable battery charging time - backlight off	Power adapter 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA Battery insert 20 h 9 V MBC-A08 20 h 20 h 12 h Rchrg. battery optional -
Supplied power supply Plug-in power supply type Input voltage power supply / power [Max] Input voltage device / power [Max] Battery / accumulator type Battery accumulator type Battery operating time Battery operating time Battery voltage Rechargeable battery Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off Rechargeable battery charging time Battery optional	Power adapter 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA Battery insert 20 h 9 V MBC-A08 20 h 20 h 12 h Rchrg. battery optional -
Supplied power supply Plug-in power supply type Input voltage power supply / power [Max] Input voltage device / power [Max] Battery / accumulator type Battery accumulator type Battery operating time Battery operating time Battery voltage Rechargeable battery Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off Rechargeable battery charging time Battery optional Environmental conditions	Power adapter 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA Battery insert 20 h 9 V MBC-A08 20 h 12 h 12 h Rchrg. battery optional - intern

# KERN MBC 15K2DEM



Elegantly-shaped baby scale – with approval for professional mobile or stationary medical use in medical diagnostics, verification optional

Humity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C
Approval	
CE mark	$\checkmark$
Conformity assessment possible ex works	1
Accuracy classe	III
Verification scale interval [e]	0,002 kg; 0,005 kg
Services (optional)	
Article number for adjustment at the location of installation	961-248
Article number for conformity assessment	965-128.
Article number for DAkkS calibration	963-128
Article number for certificate of conformity	969-517
Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	480×654×177 mm
Shipping method	Parcel service
Net weight approx.	4,6 kg
Gross weight approx.	6 kg

11,1 kg

## Pictograms

Shipping weight

STANDARD



**OPTION** 



FACTORY

