# KERN MPC 250K100M



Compact personal floor scale – with approval for professional medical use in medical diagnostics, verification optional



Category	
Brand	KERN
Product categoriy	Medical scale
Product group	Personal floor scale
Product family	MPC
Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	250 kg
Readability [d]	0,1 kg
Reproducibility	0,1 kg
Linearity	± 0,1 kg
Minimum weight [Min]	2 kg
Resolution	2.500
Tare range	249,9 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 kg (M1)
Stabilization time	3 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,1 kg
Default unit	kg
Units	kg
Conformity assessment possible	1

### Displav

Dispidy	
Display type	LCD
Display backlight	$\checkmark$
Display digit height	25 mm
Languages of the user interface	Symbol language

Construction	
Dimension display device (W×D×H)	200×130×60 mm
Dimensions weighing platform (W×D×H)	365×370×80 mm
Material housing	steel, lacquered
Material weighing plate	plastic
Material display housing	Plastics
Level indicator	$\checkmark$
Wall mount	1
Display device cable length	1,8 m
Functions	
PreTare function	1
Function for averaging under unstable weighing conditions	✓
Function for BMI calculation	1
Hold function	$\checkmark$
	3 min
Auto-off interval(s) in battery	5 min
mode/rechargeable battery mode	30 min 15 min
Tare function	manual (single & multi)
Number of keys for operation	6
Number of keys for operation	0
Interface	
Interface Interfaces	RS-232 (optional, factory)
Interfaces	
Interfaces Power Supply	factory) Power supply & battery function (battery not
Interfaces Power Supply Supplied power supply Plug-in power supply / adapter for	factory) Power supply & battery function (battery not included) Power adapter EURO
Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the	factory) Power supply & battery function (battery not included) Power adapter EURO UK
Interfaces Power Supply Supplied power supply Plug-in power supply / adapter for	factory) factory) Power supply & battery function (battery not included) Power adapter EURO UK CH
Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery	factory)  Power supply & battery function (battery not included)  Power adapter  EURO UK CH EURO EURO
Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	factory) factory) Power supply & battery function (battery not included) Power adapter EURO UK CH
Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery	factory)  Fower supply & battery function (battery not included)  Power adapter  EURO UK CH  EURO AUS
Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	factory)  Power supply & battery function (battery not included)  Power adapter  EURO UK CH  EURO AUS UK
Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	factory)  Factory)  Power supply & battery function (battery not included)  Power adapter  EURO UK CH  EURO AUS UK US
Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply /	factory)  Factory)  Power supply & battery function (battery not included)  Power adapter  EURO UK CH  EURO AUS UK US CH  100 V - 240 V, 50 / 60
Interfaces         Power Supply         Supplied power supply         Plug-in power supply type         Plug-in power supply / adapter for countries - included with the delivery         Plug-in power supply / adapter for countries - optional         Input voltage power supply / power [Max]         Input voltage device / power [Max]         Battery / accumulator type	factory) Factory) Power supply & battery function (battery not included) Power adapter EURO UK CH EURO AUS UK US CH 100 V - 240 V, 50 / 60 Hz
InterfacesPower SupplySupplied power supplyPlug-in power supply typePlug-in power supply / adapter for countries - included with the deliveryPlug-in power supply / adapter for countries - optionalPlug-in power supply / adapter for countries - optionalInput voltage power supply / power [Max] Input voltage device / power [Max]	factory) Power supply & battery function (battery not included) Power adapter EURO UK CH EURO AUS UK US CH 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA
Interfaces         Power Supply         Supplied power supply         Plug-in power supply type         Plug-in power supply / adapter for countries - included with the delivery         Plug-in power supply / adapter for countries - optional         Input voltage power supply / power [Max]         Input voltage device / power [Max]         Battery / accumulator type	factory) Factory) Power supply & battery function (battery not included) Power adapter EURO UK CH EURO AUS UK US CH 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese)
Interfaces         Power Supply         Supplied power supply         Plug-in power supply type         Plug-in power supply / adapter for countries - included with the delivery         Plug-in power supply / adapter for countries - optional         Input voltage power supply / power [Max]         Input voltage device / power [Max]         Battery / accumulator type         Battery	factory) Factory) Power supply & battery function (battery not included) Power adapter EURO UK CH EURO AUS UK US CH 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA
InterfacesPower SupplySupplied power supplyPlug-in power supply typePlug-in power supply / adapter for countries - included with the deliveryPlug-in power supply / adapter for countries - optionalPlug-in power supply / adapter for countries - optionalInput voltage power supply / power [Max]Input voltage device / power [Max]Battery / accumulator typeBatteryBattery connection	factory) Power supply & battery function (battery not included) Power adapter EURO UK CH EURO AUS UK US CH 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese) 6×1.5 V AA Battery insert

# KERN MPC 250K100M



Compact personal floor scale – with approval for professional medical use in medical diagnostics, verification optional

Rechargeable battery operating time - backlight on	20 h
Rechargeable battery operating time - backlight off	40 h
Rechargeable battery charging time	12 h
Rechargeable battery optional	Rchrg. battery optional - intern
Environmental conditions	
Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Humity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C
Approval	
CE mark	1
Conformity assessment possible ex works	$\checkmark$
Accuracy classe	111
Verification scale interval [e]	0,1 kg
Verification scale interval [e] Services (optional)	0,1 kg
	0,1 kg 961-249
Services (optional) Article number for adjustment at	
Services (optional) Article number for adjustment at the location of installation Article number for conformity	961-249
Services (optional) Article number for adjustment at the location of installation Article number for conformity assessment Article number for DAkkS	961-249 965-129

### Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	560×440×200 mm
Shipping method	Parcel service
Net weight approx.	9 kg
Gross weight approx.	11 kg
Shipping weight	10,02 kg

## Pictograms

#### STANDARD



#### OPTION



FACTORY

