KERN MPC 300K-1LM



Compact personal floor scale – with approval for professional medical use in medical diagnostics, verification optional



Category	
Brand	KERN
Product categoriy	Medical scale
Product group	Personal floor scale
Product family	MPC
Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	300 kg
Readability [d]	0,1 kg
Reproducibility	0,1 kg
Linearity	± 0,1 kg
Minimum weight [Min]	2 kg
Resolution	3.000
Tare range	299,9 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	250 kg (M1)
Stabilization time	3 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,1 kg
Default unit	kg
Units	kg
Conformity assessment possible	\checkmark

Display

Display	
Display type	LCD
Display backlight	\checkmark
Display digit height	25 mm
Languages of the user interface	Symbol language

Construction	
Dimensions completely mounted (W×D×H)	500×455×120 mm
Dimension display device (W×D×H)	200×130×60 mm
Dimensions weighing platform (W×D×H)	500×455×120 mm
Material housing	steel, lacquered
Material weighing plate	plastic
Material display housing	Plastics
Level indicator Wall mount	б Г
Display device cable length	✓ 1,8 m
Display device cable length	1,0 111
Functions	
PreTare function	1
Function for averaging under unstable weighing conditions	\checkmark
Function for BMI calculation	1
Hold function	1
Auto offictoryal(a) in bottom	3 min 5 min
Auto-off interval(s) in battery mode/rechargeable battery mode	30 min
	15 min
Tare function	manual (single & multi)
Number of keys for operation	6
Number of keys for operation	6
	6 RS-232 (optional, factory)
Interface	RS-232 (optional,
Interface Interfaces	RS-232 (optional,
Interface Interfaces Power Supply	RS-232 (optional, factory) Power supply & battery function (battery not
Interface Interfaces Power Supply Supplied power supply	RS-232 (optional, factory) Power supply & battery function (battery not included) Power adapter EURO UK
Interface Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for	RS-232 (optional, factory) Power supply & battery function (battery not included) Power adapter EURO UK CH
Interface Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the	RS-232 (optional, factory) Power supply & battery function (battery not included) Power adapter EURO UK CH EURO
Interface Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery	RS-232 (optional, factory) Power supply & battery function (battery not included) Power adapter EURO UK CH
Interface Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery	RS-232 (optional, factory) Power supply & battery function (battery not included) Power adapter EURO UK CH EURO AUS UK US
Interface Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional	RS-232 (optional, factory) Power supply & battery function (battery not included) Power adapter EURO UK CH EURO AUS UK US CH
Interface Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery	RS-232 (optional, factory) Power supply & battery function (battery not included) Power adapter EURO UK CH EURO AUS UK US
Interface Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max]	RS-232 (optional, factory) Power supply & battery function (battery not included) Power adapter EURO UK CH EURO AUS UK US CH 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA
InterfaceInterfacesPower SupplySupplied power supplyPlug-in power supply typePlug-in power supply / adapter for countries - included with the deliveryPlug-in power supply / adapter for countries - optionalInput voltage power supply / power [Max] Input voltage device / power [Max] Battery / accumulator type	RS-232 (optional, factory) Power supply & battery function (battery not included) Power adapter EURO UK CH EURO AUS UK US CH 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Alkali(-Manganese)
Interface Interfaces Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max]	RS-232 (optional, factory) Power supply & battery function (battery not included) Power adapter EURO UK CH EURO AUS UK US CH 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA

KERN MPC 300K-1LM



Compact personal floor scale – with approval for professional medical use in medical diagnostics, verification optional

Battery operating time	20 h
Rechargeable battery	MBC-A08
Rechargeable battery operating time - backlight on	20 h
Rechargeable battery operating time - backlight off	40 h
Rechargeable battery charging time	12 h
Rechargeable battery optional	Rchrg. battery optional - intern
Environmental conditions	
Environmental conditions	

Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Humity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	00 °C

1

1

Ш

0,1 kg

Pictograms

STANDARD



OPTION



FACTORY



Services (ontional)

Conformity assessment possible

Verification scale interval [e]

Approval

CE mark

ex works

Accuracy classe

Article number for adjustment at the location of installation	961-249
Article number for conformity assessment	965-129
Article number for DAkkS calibration	963-129
Article number for certificate of conformity	969-517

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	940×555×215 mm
Shipping method	Parcel service
Net weight approx.	11 kg
Gross weight approx.	15 kg
Shipping weight	22,4 kg