KERN OBE 124



Elegant, dynamic and impressive - the all-round compound microscope for schools, training and laboratories



Category	
Brand	Optics
Product categoriy	Microscope
Product group	Compound microscope
Product family	OBE-12

Construction	
Dimension (W×D×H)	360×150×320 mm
Optical system	Finite
Tube type	Trinocular
Tube angle of inclination	30°
Tube 360° rotation	✓
Tube type	Butterfly
Light distribution	20:80
Contrasting methods	Bright field Darkfield (optional) Polarisation (optional)
Standard objectives	4× 10× 40×
Lens quality	achromatic
Nosepiece screw-in locations	4
Eyepieces fixed	✓
Interpupillary distance [Min]	50 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	one-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5
Colour temperature	6000 K

Ocular	
Ocular type	Eyepiece HWF 10 x / Ø 18mm with anti-fungus, high eye point
Ocular field width	HWF
Eye point	High Eye Point
Ocular magnifications	10 x
Ocular visual field	18 mm
Ocular diameter	23,2 mm
Objective	
Objectives - Details	Objective Achromatic 10 x / 0,25 anti-fungus Objective Achromatic 4 x / 0,1 anti-fungus Objective Achromatic 40 x / 0,65 spring, anti-fungus
Objectives magnifications	4 x / 10 x / 40 x
Illumination	
Illuminance	Transmitted light
Illumination type incident light	none
Illumination type transmitted light	LED
Illumination intensity transmitted light	3 W
Illumination dimmable	Transmitted light
Filter possible	✓
Aperture diaphragm	✓
Focussing	
Field of view [Min]	0,18 mm
Field of view [Max]	4,5 mm
Torque regulation	✓
Fine drive minimum	0,002 mm
Focusing mechanism	coaxial coarse and fine drive
Power Supply	
Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for	
countries - included with the delivery	EURO
	AUS
Plug-in power supply / adapter for	UK
countries - ontional	110

US

СН

countries - optional

1

KERN OBE 124



Elegant, dynamic and impressive - the all-round compound microscope for schools, training and laboratories

Input voltage power supply / 100 V - 240 V AC 50/60

power [Max] Hz 0,3 A

Input voltage device / power [Max] $\,$ 5 V, 1 A

Environmental conditions

Storage temperature [Min] -5 °C
Storage temperature [Max] 40 °C

Approval

CE mark ✓

Packing & Shipping

Delivery time 1 d

Dimensions packaging (W×D×H) 425×340×245 mm

Net weight 4,488 kg

Shipping method Parcel service

Net weight approx. 4,6 kg

Gross weight approx. 6 kg

Shipping weight 7,1 kg

Pictograms

STANDARD











OPTION



