

KERN OBE 134C825

KERN

Our all-round compound microscope as a comprehensive digital solution for schools, training and laboratories



Category

Brand	Optics
Product category	Microscope
Product group	Digital microscope set
Product family	OBE-S

Construction

Dimension (W×D×H)	360×150×390 mm
Optical system	Finite
Tube type	Trinocular
Tube angle of inclination	30°
Tube 360° rotation	✓
Tube type	Siedentopf
Light distribution	20:80

Contrasting methods	Bright field Darkfield (optional) Polarisation (optional)
---------------------	---

Standard objectives	4× 10× 40× 100×
---------------------	--------------------------

Lens quality	achromatic
--------------	------------

Nosepiece screw-in locations	4
------------------------------	---

Eyepieces fixed	✓
-----------------	---

Interpupillary distance [Min]	50 mm
-------------------------------	-------

Interpupillary distance [Max]	75 mm
-------------------------------	-------

Diopter adjustment	one-sided
--------------------	-----------

Diopter adjustment [Min]	-5
--------------------------	----

Diopter adjustment [Max]	5
--------------------------	---

Colour temperature	6000 K
--------------------	--------

Functions

Camera - Applicable software	external (OXM 901, OXM 902)
Supported operating systems	Win XP Win Vista Win 7 Win 8 Win 10

Interface

Interfaces	USB 2.0
------------	---------

Ocular

Ocular field width	HWF
Eye point	High Eye Point
Ocular magnifications	10 x
Ocular visual field	18 mm
Ocular diameter	23,2 mm

Illumination

Illuminance	Transmitted light
Illumination type incident light	none
Illumination type transmitted light	LED
Illumination intensity transmitted light	3 W
Illumination dimmable	Transmitted light
Filter possible	✓

Focussing

Field of view [Min]	0,18 mm
Field of view [Max]	4,5 mm
Torque regulation	✓
Fine drive minimum	0,002 mm
Focusing mechanism	coaxial coarse and fine drive

Camera

Cameratype	USB2 Microscope camera - C-Mount
Camera - Resolution	5,1 MP
Camera - Sensor type	CMOS
Camera - Sensor size	1/2,5"
Camera - Colour depth	Colour
Camera - Framerate	6,8 - 55 fps
Camera- Mounting types	C-mount thread
Camera - Exposure method	Rolling Shutter

KERN OBE 134C825



Our all-round compound microscope as a comprehensive digital solution for schools, training and laboratories

Power Supply

Supplied power supply	Power supply unit
-----------------------	-------------------

Plug-in power supply type	Power adapter
---------------------------	---------------

Plug-in power supply / adapter for countries - included with the delivery	EURO
---	------

Plug-in power supply / adapter for countries - optional	AUS
	UK
	US
	CH

Input voltage power supply / power [Max]	100 - 240 V
--	-------------

Input voltage device / power [Max]	5 V, 1 A
------------------------------------	----------

Environmental conditions

Storage temperature [Min]	-5 °C
---------------------------	-------

Storage temperature [Max]	40 °C
---------------------------	-------

Approval

CE mark	✓
---------	---

Packing & Shipping

Delivery time	1 d
---------------	-----

Dimensions packaging (W×D×H)	560×440×330 mm
------------------------------	----------------

Net weight	5,768 kg
------------	----------

Shipping method	Parcel service
-----------------	----------------

Net weight approx.	6 kg
--------------------	------

Gross weight approx.	8 kg
----------------------	------

Shipping weight	16,3 kg
-----------------	---------

Pictograms

STANDARD



OPTION

