KERN OBE 134



Elegant, dynamic and impressive - the all-round compound microscope for schools, training and laboratories



С	at	е	g	0	rv
\mathbf{U}	au	\sim	Ы	<u> </u>	' y

Brand	Optics
Product categoriy	Microscope
Product group	Compound microscope
Product family	OBE-13

Construction

Dimension (W×D×H)	360×150×320 mm
Optical system	Finite
Tube type	Trinocular
Tube angle of inclination	30°
Tube 360° rotation	\checkmark
Tube type	Butterfly
Light distribution	20:80
Contrasting methods	Bright field Darkfield (optional) Polarisation (optional)
Standard objectives	4× 10× 40× 100×
Lens quality	achromatic
Nosepiece screw-in locations	4
Eyepieces fixed	\checkmark
Interpupillary distance [Min]	50 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	one-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5
Colour temperature	6000 K

Ocular	
Ocular type	Eyepiece HWF 10 x / Ø 18mm with anti-fungus, high eye point
Ocular field width	HWF
Eye point	High Eye Point
Ocular magnifications	10 x
Ocular visual field	18 mm
Ocular diameter	23,2 mm
Objective	
Objectives - Details	Objective Achromatic 10 x / 0,25 anti-fungus Objective Achromatic 100 x / 1,25 oil, spring, anti-fungus Objective Achromatic 4 x / 0,1 anti-fungus Objective Achromatic 40 x / 0,65 spring, anti- fungus
Objectives magnifications	4 x / 10 x / 40 x / 100 x
Illumination	
Illuminance	Transmitted light
Illumination type incident light	none
Illumination type transmitted light	LED
Illumination intensity transmitted light	3 W
Illumination dimmable	Transmitted light
Filter possible	✓
Aperture diaphragm	✓
Focussing	
Field of view [Min]	0,18 mm
Field of view [Max]	4,5 mm
Torque regulation	✓
Fine drive minimum	0,002 mm
Focusing mechanism	coaxial coarse and fine drive
Power Supply	
Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO

KERN OBE 134



Elegant, dynamic and impressive - the all-round compound microscope for schools, training and laboratories

Plug-in power supply / adapter for countries - optional	AUS UK US CH	
Input voltage power supply / power [Max]	100 V - 240 V AC 50/60 Hz 0,3 A	
Input voltage device / power [Max]	5 V, 1 A	
Environmental conditions		
Storage temperature [Min]	-5 °C	
Storage temperature [Max]	40 °C	
Approval		
CE mark	\checkmark	
Packing & Shipping		
Delivery time	1 d	
Dimensions packaging (W×D×H)	425×375×265 mm	
Net weight	4,488 kg	
Shipping method	Parcel service	
Net weight approx.	4,6 kg	
Gross weight approx.	6 kg	
Groop weight approx.	0	

Pictograms

STANDARD



OPTION

