

KERN OCM 168

KERN

The inverted biological laboratory microscope – also with fluorescence



Category

Brand	Optics
Product category	Microscope
Product group	Inverted microscope
Product family	OCM-1

Construction

Dimension (W×D×H)	782×304×530 mm
Optical system	Infinity
Tube type	Trinocular
Tube angle of inclination	45°
Tube type	Siedentopf
Light distribution	100:0
Contrasting methods	Bright field Phase contrast Fluorescent

Standard objectives	10× 20× 40× PH 20×
---------------------	-----------------------------

Lens quality	Infinity Plan
Nosepiece screw-in locations	5
Centring eyepiece	✓
Interpupillary distance [Min]	48 mm
Interpupillary distance [Max]	76 mm
Diopter adjustment	both-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5

Ocular

Ocular type	Eyepiece HWF 10 x / Ø 22mm with anti-fungus, high eye point
-------------	---

Ocular field width	HWF
Eye point	High Eye Point
Ocular magnifications	10 x
Ocular visual field	22 mm
Ocular diameter	30 mm

Objective

Objectives - Details	Objective Infinity Plan 10 x / 0,25 LWD, Fluor, anti-fungus Objective Infinity Plan 20 x / 0,45 LWD, Fluor, anti-fungus PH-Objective Infinity Plan 20 x / 0,45 LWD, Fluor, anti-fungus Objective Infinity Plan 40 x / 0,65 LWD, Fluor, anti-fungus
Objectives magnifications	10 x / 20 x / 40 x

Illumination

Illuminance	Reflected light Transmitted light
Illumination type incident light	LED
Illumination type transmitted light	LED
Illumination intensity incident light	5 W
Illumination intensity transmitted light	5 W
Illumination dimmable	Transmitted light
Filter possible	✓
Aperture diaphragm	✓
Field diaphragm	✓

Focussing

Field of view [Min]	0,55 mm
Field of view [Max]	2,2 mm
Torque regulation	✓
Fine drive minimum	0,002 mm
Focusing mechanism	coaxial coarse and fine drive

Power Supply

Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO

KERN OCM 168



The inverted biological laboratory microscope – also with fluorescence

Plug-in power supply / adapter for countries - optional	AUS
	UK
	US
	CH
Input voltage power supply / power [Max]	100 V - 240 V AC 50/60 Hz 0,3 A
Input voltage device / power [Max]	5 V, 1 A

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Approval

CE mark	✓
---------	---

Packing & Shipping

Delivery time	2 d
Dimensions packaging (W×D×H)	1050×590×330 mm
Shipping method	Freight
Net weight approx.	22 kg
Gross weight approx.	28 kg
Shipping weight	40,9 kg

Pictograms

STANDARD

