

KERN ORM 2CO

Digital measurement of refraction index for universal application

KERN



Measuring range refractive index [Max]	1,4200 nD
Readout refractive index	0,0001 nD
Accuracy refractive index	±0,0003 nD
Scale coffee TDS 2	✓
Measuring range coffee TDS 2 [Min]	0 %
Measuring range coffee TDS 2 [Max]	25 %
Readout coffee TDS 2	0,01 %
Accuracy coffee TDS 2	±0,2 %

Construction

Dimension (W×D×H)	121×58×25 mm
Refractometer type	Handheld refractometer
Scale - Display type	Digital
Prism lid	✓
Material prism	ZLaF3 lanthanum flint glass nd=1.85544

Functions

Averaging measurement	✓
Averaging measurement amount	15
IP protection - complete device	IP65
Auto-off interval(s) in battery mode/rechargeable battery mode	60 sec

Power Supply

Supplied power supply	Battery
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Pad + Spring
Battery capacity	1.300 mAh
Battery voltage	1,5 V

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Approval

CE mark	✓
---------	---

Services (optional)

Article number for factory calibration	961-290
--	---------

Category

Brand	Optics
Product category	Refractometer
Product group	Digital refractometer
Product family	ORM-CO

Measuring System

Area of application	Coffee
Measuring method	Total reflection
Automatic temperature compensation (ATC)	✓

Scales	Refractive index Brix Kaffee TDS 2
Measuring ranges	1,3330 nD - 1,4200 nD 0,00 % - 30,00 % 0,00 - 25,00

Readabilities [d]	0,0001 nD 0,01 % 0,01
-------------------	-----------------------------

Precision	0,0003 nD 0,20 % 0,20
-----------	-----------------------------

Appropriate calibration liquid	0 % (distilled water)
--------------------------------	-----------------------

Measurement temperature [Min] (°C)	0 °C
------------------------------------	------

Measurement temperature [Max] (°C)	40 °C
------------------------------------	-------

Brix scale	✓
------------	---

Measuring range Brix [Min]	0 %
----------------------------	-----

Measuring range Brix [Max]	30 %
----------------------------	------

Readout Brix	0,01 %
--------------	--------

Accuracy Brix	±0,2 %
---------------	--------

Scale for Refractive index	✓
----------------------------	---

Measuring range refractive index [Min]	1,3330 nD
--	-----------

KERN ORM 2CO



Digital measurement of refraction index for universal application

Packing & Shipping

Dimensions transport container (W×D×H)	170×110×50 mm
--	---------------

Delivery time	1 d
---------------	-----

Dimensions packaging (W×D×H)	170×110×50 mm
------------------------------	---------------

Shipping method	Parcel service
-----------------	----------------

Net weight approx.	0,15 kg
--------------------	---------

Gross weight approx.	0,35 kg
----------------------	---------

Shipping weight	0,31 kg
-----------------	---------

Pictograms

STANDARD

