

KERN ORM 2UN



Digital measurement of refraction index for universal application



Category

Brand	Optics
Product category	Refractometer
Product group	Digital refractometer
Product family	ORM-UN

Measuring System

Area of application	Urine
Measuring method	Total reflection
Automatic temperature compensation (ATC)	✓

Scales	Refractive index
	Brix
	Urine (spec. gravity) - cat
	Urine (spec. gravity) - dog

Measuring ranges	1,3330 nD - 1,4200 nD
	0,0 % - 50,0 %
	1,000 sgU - 1,060 sgU
	1,000 sgU - 1,060 sgU

Readabilities [d]	0,0001 nD
	0,1 %
	0,001 sgU
	0,001 sgU

Precision	0,0003 nD
	0,2 %
	0,002 sgU
	0,002 sgU

Appropriate calibration liquid	0 % (distilled water)
--------------------------------	-----------------------

Measurement temperature [Min] (°C)	0 °C
------------------------------------	------

Measurement temperature [Max] (°C)	40 °C
------------------------------------	-------

Brix scale	✓
------------	---

Measuring range Brix [Min]	0 %
----------------------------	-----

Measuring range Brix [Max]	50 %
----------------------------	------

Readout Brix	0,1 %
--------------	-------

Accuracy Brix	±0,2 %
Scale for Refractive index	✓
Measuring range refractive index [Min]	1,3330 nD
Measuring range refractive index [Max]	1,4200 nD
Readout refractive index	0,0001 nD
Accuracy refractive index	±0,0003 nD
Scale urine (s. g. dog)	✓
Measuring range urine (s. g. dog) [Min]	1,000
Measuring range urine (s. g. dog) [Max]	1,060
Readout urine (s. g. dog)	0,001
Accuracy urine (s. g. dog)	±0,002
Scale urine (s. g. cat)	✓
Measuring range urine (s. g. cat) [Min]	1,000
Measuring range urine (s. g. cat) [Max]	1,060
Readout urine (s. g. cat)	0,001
Accuracy urine (s. g. cat)	±0,002

Construction

Dimension (W×D×H)	121×58×25 mm
Refractometer type	Handheld refractometer
Scale - Display type	Digital
Prism lid	✓
Material prism	ZLaF3 lanthanum flint glass nd=1.85544

Functions

Averaging measurement	✓
Averaging measurement amount	15
IP protection - complete device	IP65
Auto-off interval(s) in battery mode/rechargeable battery mode	60 sec

Power Supply

Supplied power supply	Battery
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Pad + Spring
Battery capacity	1.300 mAh
Battery voltage	1,5 V

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

KERN ORM 2UN



Digital measurement of refraction index for universal application

Approval

CE mark	✓
---------	---

Services (optional)

Article number for factory calibration	961-290
--	---------

Packing & Shipping

Dimensions transport container (W×D×H)	170×110×50 mm
--	---------------

Delivery time	1 d
---------------	-----

Dimensions packaging (W×D×H)	170×110×50 mm
------------------------------	---------------

Shipping method	Parcel service
-----------------	----------------

Net weight approx.	0,15 kg
--------------------	---------

Gross weight approx.	0,35 kg
----------------------	---------

Shipping weight	0,31 kg
-----------------	---------

Pictograms

STANDARD

