KERN OZG 493

The specialist for jewellers and the gem industry





С	at	e	σ	0	rv
$\mathbf{\overline{\mathbf{U}}}$	uι	~	ъ	U	'y

Brand	Optics
Product categoriy	Microscope
Product group	Stereo microscope
Product family	OZG-4

Construction

Dimension (W×D×H)	310×170×350 mm
Optical system	Greenough
Tube type	Binocular
Tube angle of inclination	45°
Tube 360° rotation	1
Contrasting methods	Bright field Darkfield
Eyepieces fixed	1
Interpupillary distance [Min]	55 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	both-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5

Ocular

Ocular type	Eyepiece WF 10 x / Ø 20mm with anti-fungus	
Ocular field width	WF	
Ocular magnifications	10 x	
Ocular visual field	20 mm	
Ocular diameter	30,5 mm	
Ocular diameter	30,5 mm	

Objective

Objectives magnifications

0,7 x - 3,6 x

Illumination	
Illuminance	Reflected light Transmitted light
Illumination type incident light	Halogen
Illumination type transmitted light	Halogen
Illumination intensity incident light	10 W
Illumination intensity transmitted light	10 W
Focussing	
Field of view [Min]	5,6 mm
Field of view [Max]	28 mm
Standard total magnification [Min]	7 x
Standard total magnification [Max]	36 x
Zoom [Min]	0,7 x
Zoom [Max]	3,6 x
Torque regulation	1
Working distance	86 mm
Magnification ratio	5,1:1
Focusing mechanism	coarse drive
Stereomicroscope stand	
Stand type	pillar
Power Supply	
Power Supply Supplied power supply	Power supply unit
	Power supply unit Built-in power supply
Supplied power supply	
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the	Built-in power supply
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	Built-in power supply EURO
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply /	Built-in power supply EURO UK
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max]	Built-in power supply EURO UK 220 V
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max] Environmental conditions	Built-in power supply EURO UK 220 V
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max]	Built-in power supply EURO UK 220 V 220 V
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max] Environmental conditions Storage temperature [Min]	Built-in power supply EURO UK 220 V 220 V 220 V
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max] Environmental conditions Storage temperature [Min] Storage temperature [Max]	Built-in power supply EURO UK 220 V 220 V 220 V
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max] Environmental conditions Storage temperature [Min] Storage temperature [Max] Approval	Built-in power supply EURO UK 220 V 220 V -5 °C 40 °C
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max] Environmental conditions Storage temperature [Min] Storage temperature [Max] Approval CE mark	Built-in power supply EURO UK 220 V 220 V -5 °C 40 °C
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max] Environmental conditions Storage temperature [Min] Storage temperature [Max] Approval CE mark Packing & Shipping	Built-in power supply EURO UK 220 V 220 V -5 °C 40 °C
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max] Environmental conditions Storage temperature [Min] Storage temperature [Max] Approval CE mark Packing & Shipping Delivery time	Built-in power supply EURO UK 220 V 220 V 220 V -5 °C 40 °C

KERN OZG 493



The specialist for jewellers and the gem industry

Shipping method	Parcel service
Net weight approx.	6 kg
Gross weight approx.	6 kg
Shipping weight	8,4 kg

Pictograms

STANDARD

