KERN OZL 456



Reflected light

LED

LED

Transmitted light

The practical and flexible stereo zoom microscope with integrated LED ring illumination and large zoom range

Illuminance

CE mark

Illumination type incident light

Illumination type transmitted light



Category	
Brand	Optics
Product categoriy	Microscope
Product group	Stereo microscope
Product family	OZL-45R

Construction	
Dimension (W×D×H)	320×275×420 mm
Optical system	Greenough
Tube type	Binocular
Tube angle of inclination	45°
Tube 360° rotation	✓
Contrasting methods	Bright field
Interpupillary distance [Min]	55 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	both-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5

Ocular	
Ocular type	Eyepiece HSWF $10 \times / \emptyset$ 23mm with anti-fungus, high eye point
Ocular field width	HSWF
Eye point	High Eye Point
Ocular magnifications	10 x
Ocular visual field	23 mm
Ocular diameter	30 mm
Objective	

0,75 x - 5 x

Objectives magnifications

Illumination intensity incident light	1 W
Illumination intensity transmitted light	0,21 W
Focussing	
Field of view [Min]	5 mm
Field of view [Max]	33 mm
Standard total magnification [Min]	7,5 x
Standard total magnification [Max]	50 x
Zoom [Min]	0,75 x
Zoom [Max]	5 x
Sample height [Max]	45 mm
Torque regulation	✓
Working distance	113 mm
Magnification ratio	6,7:1
Focusing mechanism	coarse drive
Stereomicroscope stand	
Stand type	mechanical
Power Supply	
Power Supply	Power supply unit
Supplied power supply	Power supply unit
Supplied power supply Plug-in power supply type	Power supply unit Power adapter
Supplied power supply	
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for	Power adapter
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the	Power adapter
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	Power adapter EURO AUS UK
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery	Power adapter EURO AUS UK US
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional	Power adapter EURO AUS UK
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply /	Power adapter EURO AUS UK US
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max]	Power adapter EURO AUS UK US CH 100 - 240 V
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply /	Power adapter EURO AUS UK US CH 100 - 240 V
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max]	Power adapter EURO AUS UK US CH 100 - 240 V
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max]	Power adapter EURO AUS UK US CH 100 - 240 V
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max] Environmental conditions	Power adapter EURO AUS UK US CH 100 - 240 V 4,5 V
Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max] Environmental conditions Storage temperature [Min]	Power adapter EURO AUS UK US CH 100 - 240 V 4,5 V

KERN OZL 456



The practical and flexible stereo zoom microscope with integrated LED ring illumination and large zoom range

Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	490×355×325 mm
Net weight	4,585 kg
Shipping method	Parcel service
Net weight approx.	4,6 kg
Gross weight approx.	6 kg
Shipping weight	11,3 kg

Pictograms

STANDARD

