

KERN OZL 468



The flexible, affordable all-rounder with zoom function for schools, training companies, inspection authorities and laboratories



| Category | |
|------------------|-------------------|
| Brand | Optics |
| Product category | Microscope |
| Product group | Stereo microscope |
| Product family | OZL-46 |

| Construction | |
|-------------------------------|----------------|
| Dimension (W×D×H) | 300×240×420 mm |
| Optical system | Greenough |
| Tube type | Trinocular |
| Tube angle of inclination | 45° |
| Tube 360° rotation | ✓ |
| Light distribution | 100:0 |
| Contrasting methods | Bright field |
| Eyepieces fixed | ✓ |
| Interpupillary distance [Min] | 55 mm |
| Interpupillary distance [Max] | 75 mm |
| Diopter adjustment | both-sided |
| Diopter adjustment [Min] | -5 |
| Diopter adjustment [Max] | 5 |

| Ocular | |
|-----------------------|--|
| Ocular type | Eyepiece HWF 10x / Ø 20mm High Eye Point |
| Ocular field width | HWF |
| Eye point | High Eye Point |
| Ocular magnifications | 10 x |
| Ocular visual field | 20 mm |
| Ocular diameter | 30 mm |

| Objective | |
|---------------------------|---------------|
| Objectives magnifications | 0,7 x - 4,5 x |

| Illumination | |
|--|--|
| Illuminance | Reflected light Transmitted light |
| Illumination type incident light | LED |
| Illumination type transmitted light | LED |
| Illumination intensity incident light | 3 W |
| Illumination intensity transmitted light | 3 W |
| Illumination dimmable | Incident light + Transmitted light, separate |

| Focussing | |
|------------------------------------|--------------|
| Field of view [Min] | 4,4 mm |
| Field of view [Max] | 28,6 mm |
| Standard total magnification [Min] | 7 x |
| Standard total magnification [Max] | 45 x |
| Zoom [Min] | 0,7 x |
| Zoom [Max] | 4,5 x |
| Sample height [Max] | 140 mm |
| Torque regulation | ✓ |
| Working distance | 105 mm |
| Magnification ratio | 6,4:1 |
| Focusing mechanism | coarse drive |

| Stereomicroscope stand | |
|---------------------------------------|------------|
| Stand type | mechanical |
| Diameter mounting microscope head (Ø) | 76 mm |

| Power Supply | |
|---|-----------------------|
| Supplied power supply | Power supply unit |
| Plug-in power supply type | Built-in power supply |
| Plug-in power supply / adapter for countries - included with the delivery | EURO |
| | AUS |
| Plug-in power supply / adapter for countries - optional | UK |
| | US |
| | CH |
| Input voltage power supply / power [Max] | 100 - 240 V |
| Input voltage device / power [Max] | 100 - 240 V |

| Environmental conditions | |
|---------------------------|-------|
| Storage temperature [Min] | -5 °C |
| Storage temperature [Max] | 40 °C |

KERN OZL 468



The flexible, affordable all-rounder with zoom function for schools, training companies, inspection authorities and laboratories

Approval

| | |
|---------|---|
| CE mark | ✓ |
|---------|---|

Packing & Shipping

| | |
|------------------------------|----------------|
| Delivery time | 1 d |
| Dimensions packaging (W×D×H) | 510×355×290 mm |
| Net weight | 4,585 kg |
| Shipping method | Parcel service |
| Net weight approx. | 4,6 kg |
| Gross weight approx. | 6 kg |
| Shipping weight | 10,5 kg |

Pictograms

STANDARD

