KERN **PBJ 600-3M**

Multifunctional laboratory balance with single-cell weighing system, with optional verification



Category

Brand	KERN
Product category	Laboratory balance
Product group	Precision balance
Product family	PBJ

Measuring System

Weighing system	Single-Cell
Weighing capacity [Max]	620 g
USP Minimum weight of sample (k = 2, U = 0.1%)	2 g
Readability [d]	0,001 g
Automatic adjustment - Standard temperature deviation	1 °C
Automatic adjustment - Standard time interval	4 h
Reproducibility	0,001 g
Linearity	± 0,002 g
Minimum weight [Min] (verifiable)	0,1 g
Resolution	620.000
Tare range	620 g
Adjustment options	Internal calibration (automatic)
Stabilization time	2,5 s
Eccentric loading at 1/3 [Max]	0,005 g
Conformity assessment possible	✓
Construction type of the scale	Single-range balance
Units	kg g mg t gn dwt tl (Tw) tl (HK) ozt tl (Singap, Malays) ct lb oz tl (Cn) PCS % D mom
Units (if device is conformity assessed)	kg g
Default unit	g

Display

Display type	LCD
Display backlight	✓
Display digit height	14 mm
Languages of the user interface	English

Construction

Dimension housing (W×D×H)	191×317×79 mm
Dimensions completely mounted (W×D×H)	202×317×166 mm
Dimensions rectangular draught shield - inner (W×D×H)	180×193×87 mm
Dimensions rectangular draught shield - outer (W×D×H)	202×228×103 mm
Dimensions weighing surface (W×D)	113×110 mm
Dimensions weighing surface	113×110 mm
Dimensions weighing platform (W×D×H)	113×110×5 mm
Material housing	cast aluminium
Material weighing plate	stainless steel
Material draught shield	plastic
Material display housing	plastic
Material load cell(s)	aluminium
Level indicator	✓
Levelling feet adjustable	✓
Transport safety lock - bolt torque	6 Nm
Cable length	1,5 m
Load cells - number	1

Functions

PreTare function	✓
Sum memory function	✓
Recipe/summing level	Rez A (Net total)

KERN **PBJ 600-3M**

Multifunctional laboratory balance with single-cell weighing system, with optional verification

Percentage determination	✓
Dispensing function	✓
Density determination	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	visual
Underfloor weighing	Hook (included in delivery)
Function for averaging under unstable weighing conditions	✓
Time display	✓
Capacity - Display	✓
Standby function	✓
Counting function	✓
Counting resolution (laboratory conditions)	620.000
Smallest piece weight when piece counting - laboratory conditions	1 mg
Smallest piece weight when piece counting - normal conditions	10 mg
Reference quantity	5, 10, 20, 50,100, 200
Peak function	✓
Tare function	manual (multi)
Number of keys for operation	5

Interface

Interfaces	RS-232 standard - 2x

Power Supply

Supplied power supply	Power supply unit
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Power supply cable removable	removable
Input voltage device / power [Max]	12 V DC, 150 0mA
Power socket for mains adapter	Hollow plug, inside minus, Ø outside 5,5 mm, Ø inside 2,1 mm, long 9,5 mm

Environmental conditions

Ambient temperature [Min]	10 °C
Ambient temperature [Max]	30 °C
Humity of environment [Max]	80 %
Storage temperature [Min]	-10 °C
Storage temperature [Max]	50 °C

Approval

CE mark	✓
Conformity assessment possible ex works	✓
Accuracy classe	I
Verification scale interval [e]	0,01 g

Services (optional)

Article number for conformity assessment	965-201
Article number for DAkkS calibration	963-103
Article number for certificate of conformity	969-517

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	585×370×260 mm
Shipping method	Parcel service
Net weight approx.	3,6 kg
Gross weight approx.	6 kg
Shipping weight	11,3 kg
Shipping volume weight	11,3 kg

Product information

GTIN/EAN number	4045761492769
Trade number	90160010

KERN **PBJ 600-3M**

Multifunctional laboratory balance with single-cell weighing system, with optional verification

Pictograms

STANDARD



OPTION



FACTORY

