KERN PLS 20000-1F



High-quality precision scale with comfortable graphic display and enormous weighing range



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	Precision balance
Product family	PLS

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	20000 g
Weighing capacity [Max] (ct)	100000 ct
Readability [d]	0,1 g
Readability carat [d] (ct)	1 ct
Reproducibility	0,1 g
Linearity	± 0,4 g
USP Minimum weight of sample (k = 2, U = 0.1%)	200 g
Resolution	200.000
Adjustment options	Adjusting with external weight
Recommended adjusting weight	20 kg (E2)
Possible calibration points	20 kg; 10 kg
Stabilization time	3 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,4 g
Maximum creep (15 minutes)	1 g
Maximum creep (30 minutes)	2 g
Default unit	g
Units	g dwt tl (Tw) tl (HK) ozt

tl (Singap, Malays) ct mo lb oz

Display	
Display type	LCD graphic
Display backlight	✓
Display screen size	132×38 mm
Display digit height - smallest digit	4 mm
Display digit height	15 mm
Languages of the user interface	English

Construction	
Dimension housing (W×D×H)	210×340×120 mm
Dimensions completely mounted (W×D×H)	210×340×120 mm
Dimensions weighing surface (W×D)	200×175 mm
Dimensions weighing surface	200×175 mm
Dimensions weighing platform (W×D×H)	200×175×15 mm
Material housing	plastic
Material weighing plate	stainless steel
Material platform	stainless steel
Level indicator	✓
Levelling feet adjustable	✓

Functions	
PreTare function	✓
Recipe/summing level	Rez B (Net-total, memory with plain text designations + setpoint, also for printout)
Recipe weighing - number of database entries	99
Recipe weighing - number of ingredients per database entry	20
Percentage determination	✓
Density determination	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Underfloor weighing	Eye (included in delivery)
Function for averaging under unstable weighing conditions	✓
Time display	✓
Capacity - Display	✓

1

KERN PLS 20000-1F



High-quality precision scale with comfortable graphic display and enormous weighing range

Standby function	✓
Counting function	✓
Counting resolution (laboratory conditions)	40.000
Counting reference weight can be entered	✓
Smallest piece weight when piece counting - laboratory conditions	500 mg
Smallest piece weight when piece counting - normal conditions	5 g
Reference quantity	10, 25, 50, 100, n (any number of pieces)
Auto-off interval(s) in mains power mode	off 5 min 2 min 15 min
Tare function	manual (multi)
Number of keys for operation	6

Interface

Interfaces

Power Supply	
Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO AUS UK US CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	9 V DC, 1000 mA

RS-232 standard

Input voltage device / power [Max]	9 V DC, 1000 mA
Environmental conditions	
Ambient temperature [Min]	15 °C
Ambient temperature [Max]	35 °C
Humity of environment [Max]	80 %
Approval	
CE mark	✓
Services (optional)	

963-128

Article number for DAkkS

calibration

Article number for certificate of	969-517
conformity	909-317

Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	450×320×300 mm
Shipping method	Parcel service
Net weight approx.	3,2 kg
Gross weight approx.	4,4 kg
Shipping weight	8,6 kg

Pictograms

STANDARD





OPTION

