

KERN PNJ 3000-2M

The new standard in the laboratory with robust tuning fork weighing system, with optional verification



	ct
	mo
	lb
	oz
	tol
Weighing capacity [Max] (ct)	16000 ct
Readability carat [d] (ct)	0,1 ct
Default unit	g

Display	
Display type	LCD
Display backlight	✓
Display screen size	109×27 mm
Display digit height	16,5 mm
Languages of the user interface	Symbol language

Construction	
Dimension housing (W×D×H)	196×293×89 mm
Dimensions weighing surface (W×D)	190×190 mm
Dimensions weighing surface	190×190 mm
Dimensions weighing platform (W×D×H)	190×190×89 mm
Material housing	plastic
Material weighing plate	stainless steel
Level indicator	✓
Levelling feet adjustable	✓

Functions	
Percentage determination	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	visual
Capacity - Display	✓
Counting function	✓
Counting resolution (laboratory conditions)	320.000
Counting reference weight can be entered	✓
Smallest piece weight when piece counting - laboratory conditions	10 mg
Smallest piece weight when piece counting - normal conditions	100 mg
Reference quantity	10, 30, 50, 100
IP protection - display	no IP protection
IP protection - platform	no IP protection
Tare function	manual (multi)
Number of keys for operation	5

Category	
Brand	KERN
Product category	Laboratory balance
Product group	Precision balance
Product family	PNJ

Measuring System	
Weighing system	Tuning fork
Weighing capacity [Max]	3200 g
Readability [d]	0,01 g
Reproducibility	0,01 g
Linearity	± 0,02 g
Minimum weight [Min]	0,5 g
Conformity assessment possible	✓
Resolution	320.000
Tare range	3200 g
Adjustment options	Internal calibration (automatic)
Stabilization time	3 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,03 g
Units (if device is conformity assessed)	g ct
Minimum weight [Min] (ct)	5 ct
USP Minimum weight of sample (k = 2, U = 0.1%)	20 g
Construction type of the scale	Single-range balance

Units	g
	dwt
	tl (Tw)
	tl (HK)
	ozt
	tl (Singap, Malays)

KERN PNJ 3000-2M



The new standard in the laboratory with robust tuning fork weighing system, with optional verification

Interface

Interfaces	RS-232 standard
------------	-----------------

Power Supply

Supplied power supply	Power supply unit
-----------------------	-------------------

Power supply type	Power adapter
-------------------	---------------

Plug-in power supply / adapter for countries - included with the delivery	EURO
	AUS
	UK
	US
	CH

Plug-in power supply / adapter for countries - optional	EURO
	AUS
	UK
	US
	CH

Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
--	-------------------------

Power supply cable removable	removable
------------------------------	-----------

Input voltage device / power [Max]	5,95 V, 1 A
------------------------------------	-------------

Power socket for mains adapter	Hollow plug, inside plus, Ø outside 4,75 mm, Ø inside 1,7 mm, long 9,5 mm
--------------------------------	---

Battery voltage	3 V
-----------------	-----

Battery - Individual weight	6,6 g
-----------------------------	-------

Environmental conditions

Ambient temperature [Min]	5 °C
---------------------------	------

Ambient temperature [Max]	40 °C
---------------------------	-------

Humidity of environment [Max]	80 %
-------------------------------	------

Approval

CE mark	✓
---------	---

Conformity assessment possible ex works	✓
---	---

Accuracy classe	II
-----------------	----

Verification scale interval [e]	0,1 g
---------------------------------	-------

Verification scale interval [e] (ct)	1 ct
--------------------------------------	------

Services (optional)

Article number for conformity assessment	965-216
--	---------

Article number for DAkkS calibration	963-127
--------------------------------------	---------

Article number for certificate of conformity	969-517
--	---------

Packing & Shipping

Delivery time	1 d
---------------	-----

Dimensions packaging (W×D×H)	321×410×220 mm
------------------------------	----------------

Shipping method	Parcel service
-----------------	----------------

Net weight approx.	3,6 kg
--------------------	--------

Gross weight approx.	4,6 kg
----------------------	--------

Shipping weight	5,8 kg
-----------------	--------

Product information

GTIN/EAN number	4045761179868
-----------------	---------------

REACH classification	no prohibited substances
----------------------	--------------------------

Pictograms

STANDARD



OPTION



FACTORY

