## KERN TB 2000-0.1F



Practical measuring device for measuring the thickness of layers for daily use



Category	
Brand	Sauter
Product categoriy	Coating thickness measuring device
Product group	Digital coating thickness gauge
Product family	ТВ

Measuring System	
Offset accur (% of [Max])	1%
Measuring range coating thickness [d] ( $\mu$ m)	100 μm; 2000 μm
Readability coating thickness [d] (µm)	0,1 μm; 1 μm
Coating thickness gauge sensor type	FE
Test object thickness coating	Non-magnetic coatings on iron, steel, Type F
Minimum thickness coating	300 μm
Smallest sample, flat [radius]	6 mm
Smallest sample, convex [radius]	1,5 mm
Smallest sample, concave [radius]	25 mm
Sensor placement position	external
Units	μm inch (mil)
Tolerance (% of [Max])	3%

Display	
Display type	LCD

Construction	
Dimension (W×D×H)	161×69×32 mm
Dimension housing (W×D×H)	161×69×32 mm

Dimensions completely mounted (W×D×H)	161×69×32 mm
Material housing	plastic
Cable length	1 m

Functions	
Increase in measurement accuracy possible	✓

Power Supply	
Supplied power supply	Battery
Battery / accumulator type	Alkali(-Manganese)
Battery	4×1.5 V AA
Battery capacity	2.600 mAh
Battery voltage	1,5 V

Environmental conditions		
Ambient temperature [Min]	-10 °C	
Ambient temperature [Max]	40 °C	
Storage temperature [Min]	-10 °C	
Storage temperature [Max]	40 °C	

Approval		
CE mark	✓	

Services (optional)	
Article number for factory calibration	961-110

Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	265×215×71 mm
Shipping method	Parcel service
Net weight approx.	0,30 kg
Gross weight approx.	0,75 kg
Shipping weight	0,8 kg

1

## KERN TB 2000-0.1F



Practical measuring device for measuring the thickness of layers for daily use

## Pictograms

**STANDARD** 











**OPTION** 

