KERN **TE 1250-0.1N**



Ergonomic design and external measuring head for highest ease of use



Category	
Brand	Sauter
Product categoriy	Coating thickness measuring device
Product group	Digital coating thickness gauge
Product family	TE

Measuring System	
Offset accur (% of [Max])	1%
Measuring range coating thickness [d] (μ m)	100 μm; 1250 μm
Readability coating thickness [d] (µm)	0,1 μm; 1 μm
Coating thickness gauge sensor type	NFE
Test object thickness coating	Coatings on non- magnetic metals, type N
Minimum thickness coating	300 μm
Smallest sample, flat [radius]	6 mm
Smallest sample, convex [radius]	1,5 mm
Smallest sample, concave [radius]	50 mm
Sensor placement position	external
Units	μm inch (mil)
Tolerance (% of [Max])	3%

Display	
Display type	LCD
Display digit height	10 mm

Construction	
Dimension (W×D×H)	131×65×28 mm

Dimension housing (W×D×H)	131×69×28 mm
Dimensions completely mounted (W×D×H)	131×69×28 mm
Material housing	plastic

Functions	
Increase in measurement accuracy possible	✓

Power Supply	wer Supply	
Supplied power supply	Battery	
Battery / accumulator type	Alkali(-Manganese)	
Battery	4×1.5 V AAA	
Battery operating time	50 h	
Battery capacity	1.100 mAh	
Battery voltage	1,5 V	

Environmental conditions	
Ambient temperature [Min]	0 °C
Ambient temperature [Max]	50 °C
Storage temperature [Min]	0 °C
Storage temperature [Max]	50 °C

Approval		
CE mark	✓	

Services (optional)		
Article number for factory calibration	961-110	

Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	260×215×75 mm
Shipping method	Parcel service
Net weight approx.	0,20 kg
Gross weight approx.	0,85 kg
Shipping weight	0,83 kg

1

KERN **TE 1250-0.1N**



Ergonomic design and external measuring head for highest ease of use

Pictograms

STANDARD











OPTION



