

# SAUTER TU 80-0.01US

Premium ultrasonic thickness gauge

# KERN



Dimensions completely mounted (W×D×H)	130×76×32 mm
Material housing	cast aluminium
Cable length	0,9 m

## Interface

Interfaces	USB-Device
------------	------------

## Power Supply

Supplied power supply	Battery
Battery / accumulator type	Alkali(-Manganese)
Battery	2×1.5 V AA
Battery operating time	100 h
Battery capacity	3.000 mAh
Battery voltage	1,5 V
Battery - Number of cells	2
Battery - Individual weight	46 g
Battery - Total weight	92 g
Battery - Construction	Individual cells
Battery capacity (Wh)	4,5 Wh
Battery/Accu connected	not connected, enclosed

## Environmental conditions

Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	60 °C
Storage temperature [Min]	-30 °C
Storage temperature [Max]	70 °C

## Approval

CE mark	✓
---------	---

## Services (optional)

Article number for factory calibration	961-113
--	---------

## Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	315×245×85 mm
Shipping method	Parcel service
Net weight approx.	0,50 kg
Gross weight approx.	1,8 kg
Shipping weight	1,6105 kg

## Product information

GTIN/EAN number	4045761139824
Trade number	90318080
REACH classification	no prohibited substances

## Category

Brand	Sauter
Product category	Material thickness measuring device
Product group	Ultrasonic Material thickness gauge pulse-echo method
Product family	TU-US

## Measuring System

Material thickness pulse-echo [Max] (mm)	80 mm
Readability material thickness [d] (mm)	0,01 mm
Speed of sound [Min] (m/s)	1000 m/s
Speed of sound [Max] (m/s)	9999 m/s
Measuring head diameter	6 mm
Measuring head measuring frequency	7 MHz
Internal data memory: Number of value groups	20
Units	mm inch
Tolerance (% of [Max])	0,5%
Internal data memory: Number of individual values	100
Material thickness pulse-echo [Min] (mm)	0,75 mm

## Display

Display type	LCD
--------------	-----

## Construction

Dimension (W×D×H)	132×76×32 mm
Dimension housing (W×D×H)	132×76×32 mm

# SAUTER TU 80-0.01US

Premium ultrasonic thickness gauge



## Pictograms

### STANDARD



### OPTION

