SAUTER TVS 50KN80-LD



Practical set for force-displacement-measurements in laboratory and industry



| Category | |
|-------------------|----------------|
| Brand | Sauter |
| Product categoriy | Test bench |
| Product group | Test stand set |
| Product family | TVS-LD |

| Measuring System | |
|-----------------------------|---|
| Measurable length [Max] | 21 cm |
| Tolerance (measured length) | 0,5% |
| Length measuring device | Length measuring device with data interface |

| Display | |
|---------------------------------------|---------------|
| Display type | LED segments |
| Display type | 7 segment LED |
| Display digit height - smallest digit | 9 mm |

| Construction | |
|---------------------------------------|----------------------------------|
| Dimension (W×D×H) | 255×480×1670 mm |
| Dimensions completely mounted (W×D×H) | 480×255×1670 mm |
| Material housing | metal, lacquered |
| Material display housing | metal, lacquered |
| Type of drive | Stepper motor |
| Mounting - force dissipation | Threaded hole - 1 × M18, 4 × M10 |
| Mounting - force application | Threaded hole - 1 × M18, 4 × M10 |
| Generated force [Max] | 50 kN |
| Transversal movement speed [Min] | 1 mm/min |
| Transversal movement speed [Max] | 70 mm/min |

| Transversal movement speed variation | 1% |
|--------------------------------------|----------|
| Guide column(s) distance | 295 mm |
| Guide column(s) length | 113,5 cm |
| Traverse distance [Max] | 210 mm |

| Functions | |
|--|---|
| Speed display | ✓ |
| Repeat function | ✓ |
| Length measuring - zero setting | ✓ |
| Pre-added and pre-reduced length manually adjustable | ✓ |
| Limit switch | ✓ |

| Power Supply | |
|---|-----------------------------|
| Plug-in power supply type | Built-in power supply |
| Plug-in power supply / adapter for countries - optional | UK CH |
| Input voltage power supply / power [Max] | 230 V AC, 50 Hz |
| Power supply cable removable | fixed connection |
| Input voltage device / power [Max] | ~220 V - 240 V AC; 50 Hz |
| Power socket for mains adapter | Power supply cable |

| Environmental conditions | |
|---------------------------|--------|
| Storage temperature [Min] | -10 °C |
| Storage temperature [Max] | 40 °C |

| Approval | | |
|----------|---|--|
| CE mark | ✓ | |

| Packing & Shipping | |
|------------------------------|-----------------|
| Delivery time | 2 d |
| Dimensions packaging (W×D×H) | 600×410×1790 mm |
| Shipping method | Freight |
| Net weight approx. | 150 kg |
| Gross weight approx. | 175 kg |
| Shipping weight | 171 kg |

| Product information | |
|----------------------|--------------------------|
| GTIN/EAN number | 4045761343764 |
| REACH classification | no prohibited substances |

1

SAUTER TVS 50KN80-LD



Practical set for force-displacement-measurements in laboratory and industry

Pictograms

STANDARD







