KERN UID 1500K-1DM



High-resolution multi-range pallet scale with a wide range of interfaces, verification optional



| Category | |
|-------------------|------------------|
| Brand | KERN |
| Product categoriy | Industrial scale |
| Product group | Pallet scale |
| Product family | UID |

| Measuring System | |
|--------------------------------|--|
| Construction type of the scale | Multi-range balance |
| Weighing system | Strain gauge |
| Number of weighing ranges | 2 |
| Weighing capacity [Max] | 600 kg; 1500 kg |
| Readability [d] | 0,2 kg; 0,5 kg |
| Reproducibility | 0,2 kg; 0,5 kg |
| Linearity | ± 0,6 kg; 1,5 kg |
| Minimum weight [Min] | 4 kg; 10 kg |
| Resolution | 3.000, 3.000 |
| Tare range | -1500 kg |
| Adjustment options | Adjusting with external weight |
| Recommended adjusting weight | 1500 kg (M1) |
| Possible calibration points | 1000 kg |
| Stabilization time | 4 s |
| Warm-up time | 10 min; 10 min |
| Eccentric loading at 1/3 [Max] | 1 kg; 2,5 kg |
| Default unit | kg |
| Units | kg g Ib oz PCS tJ HJ |

| Units (if device is conformity assessed) | kg |
|--|----------------|
| Conformity assessment possible | ✓ |
| Loadcell type | KELI-SQB-750kg |
| Load cell connection | 4-wire |

| Display | |
|---------------------------------------|-----------------|
| Display type | LCD |
| Display type | LCD |
| Display backlight | ✓ |
| Display screen size | 110×35 mm |
| Display segments | 6 |
| Display digit height - smallest digit | 25 mm |
| Display digit height | 25 mm |
| Languages of the user interface | Symbol language |

| Construction | |
|---|----------------------|
| Dimension display device (W×D×H) | 268×115×80 mm |
| Dimensions weighing surface (W×D) | 1195×840 mm |
| Dimensions weighing surface | 1195×840 mm |
| Dimensions weighing platform (W×D×H) | 1190×840×110 mm |
| Material weighing plate | steel, powder-coated |
| Material platform | steel, powder-coated |
| Material display housing | Plastics |
| Material load cell(s) | alloyed steel |
| Level indicator | ✓ |
| Levelling feet adjustable | ✓ |
| Stand inclinable | ✓ |
| Wall mount | ✓ |
| Cable length | 5 m |
| Display device cable length | 5 m |
| Allowed cable length display device [Max] | 15 m |
| Platform Construction | welded |
| Load cells - number | 4 |
| | |

| Functions | |
|---|--------------------------|
| Recipe/summing level | Sum A |
| Percentage determination | ✓ |
| Tolerance weighing | ✓ |
| Tolerance weighing - type of signal | visual |
| Alibi memory | optional internal memory |
| Alibi memory - number of memory spaces | 250.000 |
| Function for averaging under unstable weighing conditions | ✓ |

1

KERN UID 1500K-1DM



High-resolution multi-range pallet scale with a wide range of interfaces, verification optional

| Time display | ✓ |
|--|---|
| Counting function | ✓ |
| Reference quantity | 10, 20, 50, 100, 200 |
| Hold function | ✓ |
| IP protection - display | IP65 |
| IP protection - load cell | IP67 |
| Auto-off interval(s) in battery mode/rechargeable battery mode | 3 min off 5 min 30 min 15 min |
| Auto-off interval(s) in mains power mode | 3 min off 5 min 30 min 15 min |
| Tare function | manual (single) |
| Number of keys for operation | 4 |

| Interface | |
|------------|---|
| Interfaces | RS-232 standard Ethernet (optional, factory) USB (optional, factory) WiFi (optional, factory) Alibi memory (optional, factory) USB-Host/Master (optional, factory) Verification plug (optional, factory) Bluetooth BLE (v4.0) (optional, factory) |

| Power Supply | |
|---|--|
| Supplied power supply | Power supply unit |
| Plug-in power supply type | Power adapter |
| Plug-in power supply / adapter for countries - included with the delivery | EURO UK US |
| Input voltage power supply / power [Max] | 100 V - 240 V AC 50/60 Hz 0.4 A max |
| Input voltage device / power [Max] | 12 V DC, 1000 mA |
| Battery / accumulator type | Pb |
| Battery | no battery |
| Rechargeable battery | 6 V; 1.3 Ah |
| Rechargeable battery operating time - backlight on | 26 h |
| Rechargeable battery operating time - backlight off | 43 h |

| Rechargeable battery charging time | 3 h |
|---|----------------------------------|
| Rechargeable battery optional | Rchrg. battery optional - intern |
| Environmental conditions | |
| Ambient temperature [Min] | -10 °C |
| Ambient temperature [Max] | 40 °C |
| Humity of environment [Min] | 10 % |
| Humity of environment [Max] | 95 % |
| Approval | |
| 7.661.0441 | |
| CE mark | ✓ |
| | ✓ ✓ |
| CE mark Conformity assessment possible | • |
| CE mark Conformity assessment possible ex works | ✓ |
| CE mark Conformity assessment possible ex works Accuracy classe | ✓ Ⅲ |
| CE mark Conformity assessment possible ex works Accuracy classe Verification scale interval [e] | ✓ Ⅲ |

| Packing & Shipping | |
|------------------------------|-----------------|
| Delivery time | 2 d |
| Dimensions packaging (W×D×H) | 1240×890×250 mm |
| Shipping method | Freight |
| Net weight approx. | 44 kg |
| Gross weight approx. | 65 kg |
| Shipping weight | 65 kg |

963-130

969-517

assessment

calibration

Article number for DAkkS

conformity (verification)

Article number for certificate of

KERN UID 1500K-1DM



High-resolution multi-range pallet scale with a wide range of interfaces, verification optional

Pictograms

STANDARD



OPTION



FACTORY

